


RS PRO DL 150 / 200 SC


Downlights with STEINEL DNA.

- Ideal for corridors, functional rooms or washrooms
- Colour temperature can be changed via switch on downlight
- Simple design with low installation height
- Optional mounting adapter for easy replacement during renovations
- Bluetooth mesh technology for minimal installation and maintenance effort

 **Bluetooth®
MESH**



 **professional** line



Simple connection
with Wago terminals



3000 / 4000 / 5700 K
light colour switchable















Cross-range networking of STEINEL
Bluetooth Mesh products

LED indoor light sensor

RS PRO DL 150 / 200 SC



 <p>Non-visible high-frequency sensor 360</p>	 <p>Max. Ø7 m</p>	 <p>Max. 4 m</p>	<p>Technical data RS PRO DL 150 SC</p> <p>Dimensions Ø174 x 73 mm Power 10.8 W Luminous flux 3000 K 1109 lm Luminous flux 4000 K 1177 lm Luminous flux 5700 K 1137 lm Mounting height 2–4 m Protection class (room side) IP20 (IP54) Enclosure material Plastic</p> <p>Technical data RS PRO DL 200 SC</p> <p>Dimensions Ø230 x 73 mm Power 17.3 W Luminous flux 3000 K 1996 lm Luminous flux 4000 K 2170 lm Luminous flux 5700 K 2088 lm Mounting height 2–4 m Protection class (room side) IP20 (IP54) Enclosure material Plastic</p> <p>Order Details</p> <p>RS PRO DL 150 SC 4007841 084998 RS PRO DL 200 SC 4007841 085292</p>
 <p>Soft light start</p>	 <p>Basic light</p>	 <p>Main light</p>	
 <p>Ceiling installation dimensions</p> <p>DL 150: ø 140-160 mm DL 200: ø 190-220 mm</p>	 <p>Can be networked via Bluetooth Mesh Connect</p>	 <p>Settings via STEINEL Connect App</p>	
		 <p>Order details optional mounting adapter</p> <p>Adapter ring DL 150 4007841 087364 Adapter ring DL 200 4007841 087371</p>	