













 Bluetooth Mesh	 Setting via app	 max. 4.00 m	 360°	<p>Technical data</p> Dimensions A10 Ø 190 x 69.3 mm Dimensions A20 Ø 260 x 69.3 mm Dimensions A30 Ø 330 x 69.3 mm Mains connection 220 – 240 V, 50/60 Hz Performance A10 10.7 W, 106.3 lm/W Performance A20 12.4 W, 117.8 lm/W Performance A30 20.6 W, 128.1 lm/W Luminous flux A10 1137 lm Luminous flux A20 1461 lm Luminous flux A30 2638 lm Light colour 3.000 K / 4.000 K Twilight setting 2 – 2000 lx Time setting 5 s – 60 Min. Basic light function Yes Basic lighting function Time 1 – 60 Min. Basic light adjustable 0 – 100 % Adjustable main light 0 – 100 %
 max. Ø 8 m	 2 – 2.000 lx	 5 sec – 60 min	 Basic light	
 Main light	 Softlight start	 IP54	 IK10	
3 sizes	 Ø 190 mm	 Ø 260 mm	 Ø 330 mm	

Order details

RS PRO A10 SC

3000 K, anthracite 4007841 085315
 3000 K, white 4007841 088316
 4000 K, anthracite 4007841 085308
 4000 K, white 4007841 088309

RS PRO A20 SC

3000 K, anthracite 4007841 085339
 3000 K, white 4007841 088330
 4000 K, anthracite 4007841 085322
 4000 K, white 4007841 088323

RS PRO A30 SC

3000 K, anthracite 4007841 085353
 3000 K, white 4007841 088354
 4000 K, anthracite 4007841 085346
 4000 K, white 4007841 088347