

RS PRO 5500/5550 SC.

Attractive linear luminaires - visually, technically and energetically.

Our two new RS PRO 5500 / 5550 SC linear luminaires cut an excellent figure in industrial environments as well as in passageways and office environments. In addition to their attractive appearance, their inner values are of course also impressive.

The luminaires offer pleasant lighting comfort and are also a shining example of exemplary energy efficiency - also, but not only, thanks to the Bluetooth-based benefits of STEINEL Connected Lighting. Thanks to new high-frequency technology with 24 GHz, detection ends at the wall. Added to this is the centimetre-precise range setting, which in turn ensures even greater detection sensitivity.

For better repairability and the longest possible service life, the lights are deliberately modular in design and thus follow our sustainability approach. This means that the sensor, control gear, LEDs, emergency lighting battery and emergency lighting control gear can be replaced as spare parts by a specialist in addition to the cover. The cable with 5-core through-wiring can also be inserted on both sides or from the rear. The standard SC version enables an emergency lighting function on the central battery. The SC EM version is available for a decentralised single battery solution for 3 hours of emergency lighting.

Bluetooth®
MESH

HF digital24

Components
interchangeable



Power
supply
unit

Sensor

LED card

RS PRO 5500 SC



Bluetooth® MESH				Technical data Dimensions 5500 SC 1.200 x 164 x 75 mm Dimensions 5550 SC 1.500 x 164 x 75 mm Mains connection 220 – 240V, 50/60Hz Application Wall, ceiling Performance (5500) 30,5 W, 140,6 lm/W Luminous flux (5500) 4288 lm Performance (5550) 43,5 W, 141,7 lm/W Luminous flux (5550) 6163 lm Colour rendering Ra ≥ 80 LED cooling system Passive-Thermo-Control LED-lifetime 60.000 h Sensor type High frequency, 24 GHz Electronic scalability Yes Reach Ø 8 m Angle of coverage 360° Twilight setting 2 – 2.000 lx Time setting 5 sec. – 60 Min. Basic light 10 – 100 % Main light 10 – 100 % Permanent light switchable Soft light start Yes Impact resistance IK07 Emergency light Single or central battery
Bluetooth Mesh	Setting via app	max. 4,00 m	360°	
			10-100%	
max. Ø 8 m	2 – 2.000 lx	5 sec. – 60 min	Basic light	
10-100%		///		
Main light	Soft light start	IP44	IK07	Order details RS PRO 5500 SC WW 4007841 087289 SC EM WW 4007841 087272 SC NW 4007841 086084 SC EM NW 4007841 086862
				RS PRO 5550 SC WW 4007841 087302 SC EM WW 4007841 087296 SC NW 4007841 086091 SC EM NW 4007841 086879
			Simple repair	