

Light

RS PRO 6100/6150 circular SC.

Positioned for the future.

- Long field luminaire, 1200/1500 mm, with integrated digital high-frequency sensor
- Ideal for renovating car parks, halls or garages
- Housing materials made from more than 90 per cent recycled plastic
- 360° motion detection with 8mø range, 5-wire through-wired
- Precise adjustment of range and sensitivity
- Excellent repairability: power supply, sensor and LED card replaceable
- Robust with IP65 protection and IK08 impact resistance
- All settings and networking via the free STEINEL Connect app
- Suitable for connection to a central battery



HFdigital24

Components interchangeable



Power supply unit



Sensor



LED card



RS PRO 6150 SC



				Technical data Dimensions 6100 SC 1,200x90x80 mm Dimensions 6150 SC..... 1,500x90x80 mm Mains connection 220 – 240 V, 50/60 Hz Application Wall, ceiling Colour temperature.....4000 K Performance (6100)..... 31 W, 146 lm/W Luminous flux (6100)..... 4,525 lm Performance (6150)..... 42 W, 144,9 lm/W Luminous flux (6150) 6,086 lm Colour renderingRa ≥ 80 LED cooling system.....Passive-Thermo-Control LED-lifetime..... 60,000 h Sensor type..... High frequency, 24 GHz Electronic scalabilityYes Reach Ø8 m Angle of coverage 360° Twilight setting 2 – 2,000 lx Time setting..... 5 sec. – 60 min. Basic light 10 – 100 % Main light 10 – 100 % Permanent light..... switchable Soft light start.....Yes Impact resistance.....IK08 Emergency light Single or central battery
Bluetooth Mesh	Setting via app	max. 4,00 m	360°	
max. Ø8 m	2 – 2.000 lx	5 sec. - 60 min	10- 100%	
Main light	Soft light start	IP65	IK08	
				Order details RS PRO 6100 circular SC 4007841 089832 RS PRO 6100 circular SC EM.. 4007841 089849 RS PRO 6150 circular SC 4007841 089856 RS PRO 6150 circular SC EM.. 4007841 089863
				Simple repair