### Solar light

# **XSolar SOL-O HN**

Anthracite EAN 4007841 065935 Article number 065935





365 TAGE

3000 K















( (

365 Tage Licht im Jahr

3000K warmweiß

Softlichtstart Herstellergarantie

CE

#### **Function description**

Light for free. The solar light illuminates your house number without cables or costs – with nothing but energy from the sun. At dusk, light come ON automatically. In this version too, the patented intelligent microprocessor control system and the powerful lithium-iron-phosphate rechargeable batteries provide ensure reliable illumination. 365 days of the year. With night-light function, soft light start and evening light (4 h). Including adhesive house

## **Technical specifications**

Dimensions (L x W x H)	91 x 242 x 183 mm
With lamp	Yes, STEINEL LED system
With motion detector	No
Manufacturer's Warranty	3 years
Settings via	Potentiometers
Version	Anthracite
PU1, EAN	4007841065935
Application, place	Outdoors
Application, room	outdoors, front door, courtyard & driveway
Colour	Anthracite
includes sheet of self-adhesive numbers	Yes
Installation site	wall
Impact resistance	IK03
IP-rating	IP44
Protection class	III

Mounting height max.	2,50 m
Photo-cell controller	Yes
Measured luminos flux (360°)	7 lm
Colour temperature	3000 K
Colour variation LED	SDCM5
Colour Rendering Index	80-89
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	Passive Thermo Control
Soft light start	Yes
Functions	Light sensor
Twilight setting	2 lx
Basic light level function	Yes
Basic light level function time	all night
Output	0,07 W

### Solar light

# XSolar SOL-O HN

Anthracite EAN 4007841 065935 Article number 065935



#### **Technical specifications**

Ambient temperature	-20 - 40 °C
Housing material	Aluminium
Cover material	Plastic, structured
Power supply, detail	Solar supply, no mains power required, Lithium-iron-phosphate rechargeable battery 2000 mAh

Akku-Ladung	ab 0°
Akku-Funktion	ab - 20

### **Dimension Drawing**

