

Solar light

# XSolar SOL-0 HN

Anthracite

EAN 4007841 065935

Article number 065935



365 TAGE  
LICHT

3000 K



3 years



CE

365 Tage Licht im  
Jahr

3000K warmweiß

Dämmerungsschalter

IP44

2 Lux

Softlichtstart

Herstellergarantie

Stromunabhängig

Energie sparen

CE

## Function description

Light for free. The solar light illuminates your house number without cables or costs – with nothing but energy from the sun. At dusk, light come ON automatically. In this version too, the patented intelligent microprocessor control system and the powerful lithium-iron-phosphate rechargeable batteries provide ensure reliable illumination. 365 days of the year. With night-light function, soft light start and evening light (4 h). Including adhesive house numbers.

## Technical specifications

Dimensions (L x W x H)	91 x 242 x 183 mm	Mounting height max.	2,50 m
With lamp	Yes, STEINEL LED system	Photo-cell controller	Yes
With motion detector	No	Measured luminous flux (360°)	7 lm
Manufacturer's Warranty	3 years	Colour temperature	3000 K
Settings via	Potentiometers	Colour variation LED	SDCM5
Version	Anthracite	Colour Rendering Index	80-89
PU1, EAN	4007841065935	Lamp	LED cannot be replaced
Application, place	Outdoors	LED life expectancy (max. °C)	50000 h
Application, room	outdoors, front door, courtyard & driveway	Drop in luminous flux in accordance with LM80	L70B10
Colour	Anthracite	LED cooling system	Passive Thermo Control
includes sheet of self-adhesive numbers	Yes	Soft light start	Yes
Installation site	wall	Functions	Light sensor
Impact resistance	IK03	Twilight setting	2 lx
IP-rating	IP44	Basic light level function	Yes
Protection class	III	Basic light level function time	all night
		Output	0,07 W

<https://www.steinell.de>

Subject to technical modifications

02.2024 Page 1 from 2

Solar light

# XSolar SOL-0 HN

Anthracite  
EAN 4007841 065935  
Article number 065935



## Technical specifications

Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, structured
Power supply, detail	Solar supply, no mains power required, Lithium-iron-phosphate rechargeable battery 2000 mAh

Akku-Ladung	ab 0°
Akku-Funktion	ab - 20

## Dimension Drawing

