

True Presence Multisensor Aerosol KNX



V3.0

EAN 4007841 079208

Article number 079208

high frequency
sensor 360°

Movement Ø 15 m



Presence Ø 15 m

True Presence Ø 9
m

air humidity



air pressure



brightness

CO₂

temperature



VOC

Function description

For measurably healthy indoor air. The True Presence® Multisensor Aerosol KNX detects human presence and measures light level, room temperature, humidity, air quality, volatile organic compounds (VOC) and CO₂. For the first time, this can be used as the basis for identifying and displaying a potential risk of infection as a communication object for KNX. Result: better health, better safety, better efficiency and better comfort.

Technical specifications

Dimensions (L x W x H)	123 x 123 x 33 mm	HF-system	7,2 GHz
With motion detector	Yes	Detection	also through glass, wood and stud walls
Manufacturer's Warranty	5 years	Detection angle	360 °
Settings via	ETS software, Bluetooth, Bus	Angle of aperture	160 °
With remote control	No	Sneak-by guard	Yes
PU1, EAN	4007841079208	Capability of masking out individual segments	No
Type	Presence detector	Electronic scalability	Yes
Application, place	Indoors	Mechanical scalability	No
Application, room	classroom, conference room / meeting room, one-person office, recreation room, duty room, open-plan office, hotel room, lecture hall, kitchenette, Indoors	Reach, radial	Ø 15 m (177 m ²)
Colour	white	Reach, tangential	Ø 15 m (177 m ²)
Colour, RAL	9003	Reach, presence	Ø 15 m (177 m ²)
Includes corner wall mount	No	True Presence reach	Ø 9 m (64 m ²)
Installation site	ceiling	Transmitter power	< 1 mW
Installation	Concealed wiring, Ceiling	Twilight setting	2 – 1000 lx
		Time setting	30 s – 1092 Min.
		Basic light level function	Yes

True Presence Multisensor Aerosol KNX

V3.0

EAN 4007841 079208

Article number 079208

Technical specifications

IP-rating	IP20
Ambient temperature	from 0 up to 40 °C
Material	Plastic
Mains power supply	30 V
Power consumption	1 W
Power supply, detail	KNX bus
With bus coupling	Yes
Technology, sensors	CO ₂ , High frequency, Air pressure, Air humidity, Temperature, VOC, Light sensor
Mounting height	2 – 12 m
Mounting height max.	12,00 m
Optimum mounting height	2,8 m
Montagehöhe max. True Presence Erfassung	4,00 m


Main light adjustable	0 - 100 %
Twilight setting TEACH	Yes
Constant-lighting control	Yes
KNX functions	Risk of infection, Udes air, Comfort, CO ₂ , Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Logic gate, Air pressure, Humidity output, Presence output, Day / night function, Dewpoint, Temperature output, VOC
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Interconnection via	KNX bus
Rated current	40 mA
Product category	Multisensor

Accessories

EAN 4007841 063870

Surface-mounting adapter for Multisensor

Detection Zone



Possible mounting height: 2,00 m – 12,00 m
 Orange: True Presence
 Black: movement and presence

Dimension Drawing

