

Presence detector - Professional Line

Hallway

DALI-2 APC - concealed
EAN 4007841 058029
Article number 058029



max. 25 x 3 m

2000 W

2000 W max.
(LED-ready)



IP20



10 sec - 60 min



2 - 2000 lux



2 - 4 m

iQ

iQ-mode

Teach

Teach mode



Application
Controller

5 years

manufacturer's
warranty
[steinell-professional.de/garantie](https://www.steinell.de/garantie)

Function description

The cleverer hallway sensor knows more. Perfect radial detection up to 25 m – ideal for long corridors and hallways. Reach can be adjusted in both directions. Contemporary Control PRO II design. Featuring Bluetooth technology. Interfaces for COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave).

Hallway

DALI-2 APC - concealed
 EAN 4007841 058029
 Article number 058029



Technical specifications

Type	Presence detector
Dimensions (L x W x H)	67 x 103 x 103 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Power supply, detail	max. 64 users
Sensor Technology	High frequency
Application, place	Indoors
Installation site	ceiling
Installation	Concealed wiring
Mounting height	2,00 – 4,00 m
Reach, radial	25 x 3 m (75 m ²)
Reach, tangential	25 x 3 m (75 m ²)
HF-system	5,8 GHz
Detection angle	360 °
Angle of aperture	140 °
Optimum mounting height	2,8 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	Yes
Detection	also through glass, wood and stud walls
Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	10 s – 60 Min.

Control output, Dali	Addressable / broadcast 64 electronic ballasts
Constant-lighting control	Yes
Basic light level function	Yes
Basic light level function in per cent	10 – 90 %
Basic light level function time	10 min, all day, all night
Basic light level function percentage, from	10 %
Basic light level function percentage, up to	90 %
Functions	Normal / test mode, Semi-/fully automatic, Pushbutton / switch mode, Manual ON / ON-OFF, Constant-lighting control ON-OFF
Settings via	Bluetooth
With remote control	No
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
IP-rating	IP20
Material	Plastic
Ambient temperature	-20 – 50 °C
Application, room	Indoors, corridor / aisle
Colour	white
Colour, RAL	9003
IDs, certificates	DALI-2
Manufacturer's Warranty	5 years
Version	DALI-2 APC - concealed
PU1, EAN	4007841058029


Hallway

DALI-2 APC - concealed

EAN 4007841 058029

Article number 058029

Detection Zone



Mögliche Montagehöhe: 2,00 m – 4,00 m
Orange: radial und tangential

Dimension Drawing

