

Presence detector - Professional Line

HF 360-2

DALI-2 APC - concealed
EAN 4007841 064266
Article number 064266



high frequency
sensor 360°



max. Ø 12 m



IP20



mounting height
max. 4 m



2 - 2000 lux



10 sec - 60 min

iQ

iQ-mode

Teach

Teach mode



Application
Controller



plastic free
packaging

Function description

Smart surveillance professional. The HF 360-2 from the new Control PRO 2 range. Modern look and intelligent 360° HF sensor technology – ideal for stairwells and toilet facilities with cubicles. Conveniently adjusted and interconnected via Bluetooth. Interfaces: COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave). Mounting height up to 4 m. Reach: 12 m.

HF 360-2

DALI-2 APC - concealed
 EAN 4007841 064266
 Article number 064266



Technical specifications

Type	Presence detector
Dimensions (L x W x H)	61 x 103 x 103 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Power supply, detail	max. 64 users
Number of Dali users	64
Sensor Technology	High frequency
Application, place	Indoors
Installation site	ceiling
Installation	Concealed wiring
Mounting height	2,50 – 4,00 m
Reach, radial	Ø 12 m (113 m ²)
Reach, tangential	Ø 12 m (113 m ²)
Reach, detail	1 or 2 detection directions can be masked out by stickers for adjustment to the room situation.
HF-system	5,8 GHz
Detection angle	360 °
Angle of aperture	140 °
Optimum mounting height	2,8 m
Mechanical scalability	No
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	Yes
Detection	also through glass, wood and stud walls
Twilight setting TEACH	Yes

Twilight setting	2 – 2000 lx
Time setting	10 s – 60 Min.
Control output, Dali	Addressable / broadcast 64 electronic ballasts
Constant-lighting control	Yes
Basic light level function	Yes
Basic light level function in per cent	3 – 90 %
Basic light level function time	1-60 min, all night
Functions	Selecting programmed lighting scenarios, Semi-/fully automatic, Constant-lighting control ON-OFF, Lighting scenario, Manual ON / ON-OFF, Neighbouring group function, Normal / test mode, TouchDIM function
Settings via	Bluetooth
With remote control	No
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
IP-rating	IP20
Material	Plastic
Ambient temperature	-25 – 50 °C
Application, room	function room / ancillary room, kitchenette, stairwell, WC / washroom, Indoors
Colour	white
Colour, RAL	9003
IDs, certificates	DALI-2
Manufacturer's Warranty	5 years
Version	DALI-2 APC - concealed
PU1, EAN	4007841064266
Technology, sensors	High frequency, Photo-cell controller


HF 360-2

DALI-2 APC - concealed

EAN 4007841 064266

Article number 064266

Detection Zone



Mögliche Montagehöhe: 2,50 m – 4,00 m
Orange: radial und tangential

Dimension Drawing

