

HF 360-2

DALI-2 Input Device - surface
 EAN 4007841 064297
 Article number 064297



Hochfrequenz
Sensor 360°



Max. Ø 12 m



IP20



Montagehöhe max. 4
m



2 - 2000 Lux



Temperatur



Luftfeuchte



Input Device



Plastikfreie
Verpackung



Energie sparen

Function description

Smart surveillance professional. The HF 360-2 from the new Control PRO 2 range. Modern look and intelligent 360° HF sensor technology – ideal for stairwells and toilet facilities with cubicles. Conveniently adjusted and interconnected via Bluetooth. Interfaces: COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave). Mounting height up to 4 m. Reach: 12 m.

Technical specifications

Dimensions (L x W x H)	57 x 123 x 123 mm	Mounting height max.	4,00 m
With motion detector	Yes	Optimum mounting height	2,8 m
Manufacturer's Warranty	5 years	HF-system	5,8 GHz
Settings via	Bluetooth, Bus	Detection	also through glass, wood and stud walls
With remote control	No	Detection angle	360 °
Version	DALI-2 Input Device - surface	Angle of aperture	140 °
PU1, EAN	4007841064297	Sneak-by guard	Yes
Type	Presence detector	Capability of masking out individual segments	No
Application, place	Indoors	Electronic scalability	Yes
Application, room	function room / ancillary room, kitchenette, stairwell, WC / washroom, Indoors	Mechanical scalability	No
Colour	white	Reach, radial	Ø 12 m (113 m ²)
Colour, RAL	9003	Reach, tangential	Ø 12 m (113 m ²)
Includes corner wall mount	No	Transmitter power	< 1 mW
Installation site	ceiling	Twilight setting	2 – 2000 lx
Installation	Surface wiring, Ceiling	Basic light level function	No
IP-rating	IP20	Main light adjustable	No

HF 360-2

DALI-2 Input Device - surface
EAN 4007841 064297
Article number 064297



Technical specifications


Ambient temperature	-25 – 50 °C
Material	Plastic
Mains power supply	12.5 – 22 V
Power supply, detail	DALI bus
Steuerausgang, Dali	Addressable/slave
With bus coupling	Yes
Technology, sensors	High frequency, Light sensor, Temperature, Air humidity
Mounting height	2,50 – 4,00 m

Twilight setting TEACH	No
Constant-lighting control	No
Interconnection	Yes
Type of interconnection	Master/slave
Interconnection via	Bluetooth, DALI bus
Max. Current consumption according to IEC 62386-101	84 mA
Typical current consumption at 16V input voltage	21 mA
Max. Current consumption at 10V input voltage in regular operation	38 mA

HF 360-2


DALI-2 Input Device - surface
EAN 4007841 064297
Article number 064297

Detection Zone



Possible mounting height: 2,50 m - 4,00 m
Orange: radial and tangential

Dimension Drawing



Circuit diagram

