

Hallway

IP - surface

EAN 4007841 066154

Article number 066154



max. 25 x 3 m



IP20



brightness



temperature



air humidity



2 - 12 m

5 years

manufacturer's warranty
steinel-professional.de/
garantie



CE

Function description

The cleverer hallway sensor knows more. Perfect radial detection up to 25 m – ideal for long corridors and hallways. Reach can be adjusted in both directions. Contemporary Control PRO II design. Featuring Bluetooth technology. Interfaces for COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave).

Technical specifications

| | | | |
|----------------------------|---------------------------|---|---|
| Dimensions (L x W x H) | 62 x 123 x 123 mm | Mounting height | 2,00 – 4,00 m |
| With motion detector | Yes | Mounting height max. | 4,00 m |
| Manufacturer's Warranty | 5 years | Optimum mounting height | 2,8 m |
| Settings via | Bluetooth, Web-Interface | HF-system | 5,8 GHz |
| With remote control | No | Detection | also through glass, wood and stud walls |
| Version | IP - surface | Detection angle | Aisle, 360 ° |
| PU1, EAN | 4007841066154 | Angle of aperture | 140 ° |
| Type | Presence detector | Sneak-by guard | Yes |
| Application, place | Indoors | Capability of masking out individual segments | No |
| Application, room | Indoors, corridor / aisle | Electronic scalability | Yes |
| Colour | white | Mechanical scalability | No |
| Colour, RAL | 9003 | Reach, radial | 25 x 3 m (75 m ²) |
| Includes corner wall mount | No | Reach, tangential | 25 x 3 m (75 m ²) |
| Installation site | ceiling | Transmitter power | < 1 mW |
| Installation | Surface wiring, Ceiling | Basic light level function | No |
| IP-rating | IP20 | Main light adjustable | No |
| Ambient temperature | from -20 up to 50 °C | | |

Hallway

IP - surface
EAN 4007841 066154
Article number 066154




Technical specifications

| | |
|----------------------|---|
| Material | Plastic |
| Mains power supply | 18 – 55 V |
| Power supply, detail | Passive PoE SELV, standard PoE (IEEE 802.3 af) |
| Technology, sensors | High frequency, Light sensor, Temperature, Air humidity |

| | |
|---------------------------|-------------------|
| Twilight setting TEACH | No |
| Constant-lighting control | No |
| Interconnection | Yes |
| Interconnection via | Bluetooth, LAN |
| Product category | Presence detector |

Detection Zone



Possible mounting height: 2,00 m – 4,00 m
Orange: radial and tangential

Dimension Drawing

