

Photo-cell-controlled light

# LN 710 N

Anthracite

EAN 4007841 053161

Article number 053161



3000 K



Twilight switch



IP44



soft light start



energy saving

3 years

manufacturer's  
warranty  
[steinel.de/garantie3y](http://steinel.de/garantie3y)




CE



TüV Nord GS



Light source not  
exchangeable



Control gear not  
exchangeable

## Function description

Brilliant design on the cutting edge. The LN 710 N outdoor light scores with a trailblazing design. In connection with the elegant light gradient, the futuristic shape of the light creates a unique light pattern. The warm-white light (3000 K) adds a harmonious air to the overall sculptured effect. The LN 710 N outdoor light is fitted with an intelligent 360° infrared sensor and has four sensor programs, including night-light functions and soft light start. In the manual override mode, the LN 710 N stays ON for four hours. A second version is also available without motion detector - the LN 710 N. This version is fitted with a photo-cell controller and provides automatic illumination at night as well as an optional night economy mode.

Photo-cell-controlled light

# LN 710 N

Anthracite

EAN 4007841 053161

Article number 053161



## Technical specifications

Dimensions (L x W x H)	140 x 260 x 63 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	Light sensor
Output	8,3 W
Interconnection	No
Slave mode/selectable	No
Luminous flux	729 lm
Stroboskop-Effekt (SVM)	1,5 SVM
Efficiency	88 lm/W
Colour temperature	3000 K
Colour Rendering Index	= 82
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
LED life expectancy (25 °C)	> 60000 h
Life expectancy of power supply unit (25 °C)	> 60000 h
Base	without
LED cooling system	Passive Thermo Control
With motion detector	No
Capability of masking out individual segments	No

Electronic scalability	No
Mechanical scalability	No
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Basic light level function	No
Functions	Light sensor
Soft light start	Yes
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, opal
Manufacturer's Warranty	3 years
Settings via	Potentiometers
With remote control	No
Installation site	wall
Cover material	sticker
Version	Anthracite
PU1, EAN	4007841053161

## Dimension Drawing

