

Floodlight without sensor

# LS 150

white

EAN 4007841 069223

Article number 069223



LED

30 years (Ø 4,5h / day)

4000 K

4000K neutral white



IP44

3 years

manufacturer's warranty  
steinel.de/garantie3y



CE



energy saving



plastic free packaging



Light source not exchangeable



Control gear not exchangeable

## Function description

Beautiful. Bright. Ideal for courtyards and driveways: the LS 150 M LED spotlight without sensor. Neutral white light (4,000 K), {luminous flux}, 14,7 W. Adjustable 80° horizontally and 150° vertically. The spotlight is switched on and off manually by a switch. Protection class IP 44. Colour version: black and white.

## Technical specifications

|                                     |                          |
|-------------------------------------|--------------------------|
| Dimensions (L x W x H)              | 167 x 157 x 178 mm       |
| Mains power supply                  | 220 – 240 V / 50 – 60 Hz |
| Output                              | 14,7 W                   |
| Interconnection                     | No                       |
| Luminous flux                       | 1760 lm                  |
| Efficiency (without shade/diffuser) | 77 lm/W                  |
| Colour temperature                  | 4000 K                   |
| Colour variation LED                | SDCM3                    |
| Colour Rendering Index              | 80-89                    |
| With lamp                           | Yes, STEINEL LED system  |
| Lamp                                | LED cannot be replaced   |
| LED life expectancy (max. °C)       | 50000 h                  |
| Base                                | without                  |
| LED cooling system                  | Passive Thermo Control   |

|                            |               |
|----------------------------|---------------|
| With motion detector       | No            |
| Basic light level function | No            |
| Main light adjustable      | No            |
| Soft light start           | No            |
| Impact resistance          | IK03          |
| IP-rating                  | IP44          |
| Protection class           | I             |
| Ambient temperature        | -10 – 30 °C   |
| Housing material           | Aluminium     |
| Manufacturer's Warranty    | 3 years       |
| Installation site          | wall          |
| Version                    | white         |
| PU1, EAN                   | 4007841069223 |

Floodlight without sensor

# LS 150

white

EAN 4007841 069223

Article number 069223



## Dimension Drawing

