

Hallway

V3.5 KNX - Surface wiring
 EAN 4007841 079079
 Article number 079079



max. 25 x 3 m



IP20



10 - 1000 lux



10 sec - 30 min



ideal 2,5 - 3,5 m

Teach

Teach mode



KNX

5 years

manufacturer's warranty steinel-professional.de/garantie



CE

Function description

The cleverer hallway sensor knows more. Perfect radial detection up to 25 m – ideal for long corridors and hallways. Reach can be adjusted in both directions. Contemporary Control PRO II design. Featuring Bluetooth technology. Interfaces for COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave).

Technical specifications

Dimensions (L x W x H)	62 x 123 x 123 mm	Optimum mounting height	2,8 m
With motion detector	Yes	HF-system	5,8 GHz
Manufacturer's Warranty	5 years	Detection	also through glass, wood and stud walls
Settings via	ETS software, Bluetooth, Bus	Detection angle	Aisle, 360 °
With remote control	No	Angle of aperture	140 °
Version	KNX - Surface wiring	Sneak-by guard	Yes
PU1, EAN	4007841079079	Capability of masking out individual segments	No
Type	Presence detector	Electronic scalability	Yes
Application, place	Indoors	Mechanical scalability	No
Application, room	Indoors, corridor / aisle	Reach, radial	25 x 3 m (75 m ²)
Colour	white	Reach, tangential	25 x 3 m (75 m ²)
Colour, RAL	9003	Transmitter power	< 1 mW
Includes corner wall mount	No	Twilight setting	10 – 1000 lx
Installation site	ceiling	Time setting	10 s – 1092 Min.
Installation	Surface wiring, Ceiling	Basic light level function	Yes
IP-rating	IP20		
Ambient temperature	from -25 up to 50 °C		

Hallway


V3.5 KNX - Surface wiring
 EAN 4007841 079079
 Article number 079079

Technical specifications

Material	Plastic
Mains power supply	30 V
Power consumption	0,7 W
Power supply, detail	KNX bus
With bus coupling	Yes
Technology, sensors	High frequency, Light sensor
Mounting height	2 – 4 m
Mounting height max.	4,00 m

Main light adjustable	0 - 100 %
Twilight setting TEACH	Yes
Constant-lighting control	Yes
KNX functions	Comfort, Photo-cell controller, Individual pyro evaluation, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function, Dewpoint, Logic gate, Humidity output, Temperature output
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Interconnection via	KNX bus
Rated current	30 mA
Product category	Presence detector

Detection Zone



Possible mounting height: 2,50 m – 3,50 m
 Orange: radial and tangential

Dimension Drawing

