Presence detector - Professional Line

Hallway

V3.5 KNX - Concealed wiring EAN 4007841 079086 Article number 079086















Settings via App







air humi

KNX

Function description

The cleverer hallway sensor knows more. Perfect radial detection up to 25 m – ideal for long corridors and hallways. Reach can be adjusted in both directions. Contemporary Control PRO II design. Featuring Bluetooth technology. Interfaces for COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave).

Presence detector - Professional Line

Hallway

V3.5 KNX - Concealed wiring EAN 4007841 079086 Article number 079086



Technical specifications

| Туре | Presence detector |
|---|---|
| Dimensions (L x W x H) | 67 x 103 x 103 mm |
| Mains power supply | 30 V |
| Power consumption | 0,7 W |
| Power supply, detail | KNX bus |
| Sensor Technology | High frequency |
| Application, place | Indoors |
| Installation site | ceiling |
| Installation | Concealed wiring |
| Mounting height | 2 – 4 m |
| Reach, radial | 25 x 3 m (75 m ²) |
| Reach, tangential | 25 x 3 m (75 m ²) |
| HF-system | 5,8 GHz |
| Detection angle | 360 ° |
| Angle of aperture | 140 ° |
| Optimum mounting height | 2,8 m |
| Mechanical scalability | No |
| Sneak-by guard | Yes |
| Capability of masking out individual segments | No |
| Electronic scalability | Yes |
| Detection | also through glass, wood and stud walls |

| Twilight setting TEACH | Yes |
|----------------------------|--|
| Twilight setting | 10 – 1000 lx |
| Time setting | 10 s – 1092 Min. |
| Constant-lighting control | Yes |
| Basic light level function | Yes |
| KNX functions | Comfort, Photo-cell controller, Individual pyro evaluation, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function, Dewpoint, Logic gate, Humidity output, Temperature output |
| With bus coupling | Yes |
| Settings via | ETS software, Bluetooth, Bus |
| With remote control | No |
| Interconnection | Yes |
| Type of interconnection | Master/master, Master/slave |
| IP-rating | IP20 |
| Material | Plastic |
| Ambient temperature | -25 – 50 °C |
| Application, room | Indoors, corridor / aisle |
| Colour | white |
| Colour, RAL | 9003 |
| Manufacturer's Warranty | 5 years |
| Version | KNX - Concealed wiring |
| PU1, EAN | 4007841079086 |
| Technology, sensors | High frequency, Light sensor |

Dimension Drawing

