

DualTech

V3 KNX - in-ceiling installation
 EAN 4007841 079581
 Article number 079581



ultrasonic sensor
360°



infrared sensor
360°



max. Ø 6 m
presence



KNX 4 channel



IP20



ideal 2,5 - 3,5 m



indoor sensor



iQ-mode



Teach mode



energy saving

Function description

The best of both worlds. Combined in one detector. Ultrasonic presence detector DualTech KNX, ideal for offices, conference rooms and class rooms. 36 sq.m. presence zone, ultrasonic technology provides reliable detection behind objects regardless of temperature, additional detection capability with PIR technology, electronic adjustment for ultrasonic reach, with digital BUS interface for controlling 4 lighting channels and HVAC.

Technical specifications

Dimensions (L x W x H)	103 x 120 x 120 mm
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	ETS software, Remote control, Bus, Smart Remote
Version	KNX - in-ceiling installation
PU1, EAN	4007841079581
Type	Presence detector
Application, place	Indoors
Application, room	classroom, one-person office, open-plan office, conference room / meeting room, duty room, recreation room, Indoors
Colour	white
Colour, RAL	9010
Includes corner wall mount	No
Installation site	ceiling
Package content	1

Ultrasonic technology	40 kHz
Detection angle	360 °
Angle of aperture	180 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	Ø 10 m (79 m ²)
Reach, tangential	Ø 10 m (79 m ²)
Reach, presence	Ø 6 m (28 m ²)
Twilight setting	10 – 1000 lx
Time setting	0 s – 1092 Min.
Basic light level function	Yes
Basic light level function time	1-255 min
Main light adjustable	0 - 100 %
Twilight setting TEACH	Yes

DualTech

V3 KNX - in-ceiling installation
 EAN 4007841 079581
 Article number 079581



Technical specifications

Installation	In-ceiling installation, Ceiling
IP-rating	IP20
Ambient temperature	from -25 up to 55 °C
Material	Plastic
Mains power supply	30 V
Power consumption	0,7 W
With bus coupling	Yes
Technology, sensors	Ultrasonic, passive infrared, Light sensor
Mounting height	2,50 – 3,5 m
Mounting height max.	3,50 m
Optimum mounting height	2,8 m

Constant-lighting control	Yes
KNX functions	Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function, Logic gate
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Interconnection via	KNX bus
Rated current	17,5 mA
KNX Medium	TP 256
KNX Secure	No
Product category	Presence detector


Accessories

EAN 4007841 003036	Control PRO guard cage
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 593018	Service remote control RC6 KNX
EAN 4007841 592912	User remote control RC7 KNX

DualTech


V3 KNX - in-ceiling installation
EAN 4007841 079581
Article number 079581

Detection Zone



Possible mounting height: 2,50 m - 3,50 m
Orange: presence and tangential
Black: radial

Dimension Drawing 1



Dimension Drawing 2

