

EAN 4007841 080662

Article number



LED

long life LED
50.000 h

3000 K

3000K
warm-white



IP54



5 - 200 lux



IK07



Ideal 2 m



energy saving

3 years

manufacturer's
warranty
steinel.de/garantie

CE

CE



TüV Nord GS

Function description

Technical specifications

Dimensions (L x W x H)	56 x 300 x 195 mm
Mains power supply	230 – 240 V / 50 – 60 Hz
Sensor Technology	Light sensor
Output	4,5 W
Interconnection	No
Slave mode/selectable	No
Luminous flux	350 lm
Efficiency	78 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
Colour Rendering Index	80-89
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
Base	without
LED cooling system	Passive Thermo Control
With motion detector	No
Sneak-by guard	No

Capability of masking out individual segments	No
Electronic scalability	No
Mechanical scalability	No
Photo-cell controller	Yes
Twilight setting	5 – 200 lx
Basic light level function	No
Main light adjustable	No
Soft light start	No
Impact resistance	IK07
IP-rating	IP54
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Plastic
Cover material	Plastic, opal
Manufacturer's Warranty	3 years
includes sheet of self-adhesive numbers	No
Settings via	Potentiometers
With remote control	No
PU1, EAN	4007841080662

EAN 4007841 080662

Article number

Dimension Drawing

