

HF 360

COM1 - in-ceiling installation
 EAN 4007841 079512
 Article number 079512



high frequency sensor 360°



max. Ø 12 m

2000 W

max. 2000 W



IP20



ideal 2.5 - 3.5 m



indoor sensor

iQ

iQ-mode

Teach

Teach mode



energy saving

5 years

manufacturer's warranty steinel-professional.de/garantie

Function description

Doesn't miss a thing. HF-presence detector Presence Control PRO HF 360 COM1 for indoors, ideal for WCs with toilet cubicles, changing rooms, stairwells, multi-storey car parks, kitchens, installation height up to 3.5 m, for switching light 'ON' and 'OFF', 1 – 12 m reach, reach is electronically adjustable and can be limited in two directions, detection regardless of temperature, HF-sensor technology also detects movement through glass, wood and stud walls.

Technical specifications

Dimensions (L x W x H)	94 x 120 x 120 mm	HF-system	5,8 GHz
Manufacturer's Warranty	5 years	Detection	also through glass, wood and stud walls
Settings via	Remote control, DIP switches, Potentiometers, Smart Remote	Detection angle	360 °
With remote control	No	Angle of aperture	140 °
Version	COM1 - in-ceiling installation	Sneak-by guard	Yes
PU1, EAN	4007841079512	Capability of masking out individual segments	Yes
Type	Presence detector	Electronic scalability	Yes
Application, place	Indoors	Mechanical scalability	No
Application, room	function room / ancillary room, kitchenette, stairwell, WC / washroom, Indoors	Reach, radial	Ø 12 m (113 m ²)
Colour	white	Reach, tangential	Ø 12 m (113 m ²)
Colour, RAL	9010	Transmitter power	< 1 mW
Includes corner wall mount	No	Functions	Normal / test mode, Semi-/fully automatic, Pushbutton / switch mode, Manual ON / ON-OFF
Installation site	ceiling	Twilight setting	10 – 1000 lx
Installation	In-ceiling installation, Ceiling	Time setting	30 s – 30 Min.
IP-rating	IP20		

HF 360

COM1 - in-ceiling installation
EAN 4007841 079512
Article number 079512



Technical specifications

Ambient temperature	from -25 up to 55 °C	Basic light level function	No
Material	Plastic	Main light adjustable	No
Mains power supply	230 V / 50 – 60 Hz	Twilight setting TEACH	Yes
Technology, sensors	High frequency, Light sensor	Constant-lighting control	No
Mounting height	2,50 – 3,50 m	Interconnection	Yes
Mounting height max.	3,50 m	Type of interconnection	Master/master, Master/slave
Optimum mounting height	2,8 m	Interconnection via	Cable
		Product category	Presence detector


Accessories

EAN 4007841 003036	Control PRO guard cage
EAN 4007841 009151	Remote control Smart Remote
EAN 4007841 559410	Service remote control RC8

HF 360


COM1 - in-ceiling installation
EAN 4007841 079512
Article number 079512

Detection Zone




Possible mounting height: 2,50 m - 3,50 m
Orange: radial and tangential


Dimension Drawing 1



Dimension Drawing 2




Master circuit diagram



HF 360

COM1 - in-ceiling installation
EAN 4007841 079512
Article number 079512

Master/master interconnection circuit diagram



Master/slave interconnection circuit diagram

