

IR Quattro 8m

V3 KNX - in-ceiling installation
 EAN 4007841 079390
 Article number 079390



infrared sensor



max. 4 x 4 m presence



KNX 4 channel



IP20



ideal 2.5 - 8 m



indoor sensor



iQ-mode



Teach mode



energy saving

5 years

manufacturer's warranty steinel-professional.de/garantie

Function description

Squaring the circle. Infrared presence detector Presence Control PRO IR Quattro KNX for indoors, ideal for small offices, store, service and utility rooms, washrooms and WCs, installation height up to 8 m, with digital BUS interface for controlling 4 lighting channels and HVAC, 1760 switching zones for excellent detection quality, square presence detection zone covering 16 m², mechanically scalable.

Technical specifications

| | |
|----------------------------|--|
| Dimensions (L x W x H) | 113 x 120 x 120 mm |
| With motion detector | Yes |
| Manufacturer's Warranty | 5 years |
| Settings via | ETS software, Remote control, Bus, Smart Remote |
| Version | KNX - in-ceiling installation |
| PU1, EAN | 4007841079390 |
| Type | Presence detector |
| Application, place | Indoors |
| Application, room | one-person office, conference room / meeting room, duty room, recreation room, changing room, function room / ancillary room, kitchenette, Indoors |
| Colour | white |
| Colour, RAL | 9010 |
| Includes corner wall mount | No |
| Installation site | ceiling |
| Installation | In-ceiling installation, Ceiling |

| | |
|---|------------------------------|
| Detection angle | 360 ° |
| Angle of aperture | 100 ° |
| Sneak-by guard | Yes |
| Capability of masking out individual segments | No |
| Electronic scalability | No |
| Mechanical scalability | Yes |
| Reach, radial | 5 x 5 m (25 m ²) |
| Reach, tangential | 7 x 7 m (49 m ²) |
| Reach, presence | 4 x 4 m (16 m ²) |
| Switching zones | 1760 switching zones |
| Twilight setting | 10 – 1000 lx |
| Time setting | 0 s – 1092 Min. |
| Basic light level function | Yes |
| Main light adjustable | 0 - 100 % |
| Twilight setting TEACH | Yes |
| Constant-lighting control | Yes |

IR Quattro 8m

V3 KNX - in-ceiling installation
EAN 4007841 079390
Article number 079390



Technical specifications

| | | | |
|-------------------------|---|-------------------------|--|
| IP-rating | IP20 | | |
| Ambient temperature | from 0 up to 40 °C | KNX functions | Photo-cell controller, Basic light level function, Light level, HVAC output, Constant-lighting control, Light output 4x, Presence output, Day / night function, Logic gate |
| Material | Plastic | | |
| With bus coupling | Yes | Interconnection | Yes |
| Technology, sensors | Photo-cell controller, passive infrared | Type of interconnection | Master/master, Master/slave |
| Mounting height | 2,50 – 8,00 m | Interconnection via | KNX bus |
| Mounting height max. | 8,00 m | Rated current | 10 mA |
| Optimum mounting height | 2,8 m | Product category | Presence detector |


Accessories

| | |
|--------------------|--------------------------------|
| EAN 4007841 593018 | Service remote control RC6 KNX |
| EAN 4007841 003036 | Control PRO guard cage |
| EAN 4007841 009151 | Remote control Smart Remote |
| EAN 4007841 592912 | User remote control RC7 KNX |

IR Quattro 8m


V3 KNX - in-ceiling installation
EAN 4007841 079390
Article number 079390

Detection Zone



Possible mounting height: 2,50 m - 8,00 m
Orange: presence
Black: tangential

Dimension Drawing 1



Dimension Drawing 2

