## **XLED PRO ONE Max**

without motion detector - anthracite EAN 4007841 069520 Article number 069520







3000 K

















ong life LED 50.000 h

3000K warm-white

IP44

180° vertical

Indoor/Outdoo

networkable vi

energy savin

ight source not exchangeable

Control gear no exchangeable

CE

#### **Function description**

Floodlight redefined. The XLED PRO ONE floodlight without sensor, which can be swivelled vertically through 180° and comes in a stylish aluminium housing, ensures daylight illumination of large areas with warm white 3000 K and 6093 lm at 49,4 W. Suitable for manual switch operation and for cable-based networking in conjunction with a sensor version. With optional surface-mounted adapter. Available in white or anthracite. 5-year guarantee.

## **Technical specifications**

| Dimensions (L x W x H)     | 202 x 259 x 226 mm   |
|----------------------------|--|
| With lamp                  | Yes, STEINEL LED system  |
| With motion detector       | No   |
| Manufacturer's Warranty    | 5 years  |
| Version                    | without motion detector - anthracite   |
| PU1, EAN                   | 4007841069520  |
| Application, place         | Outdoors   |
| Application, room          | outdoors, garden, front door,<br>courtyard & driveway, all round the<br>building |
| Colour                     | Anthracite   |
| Includes corner wall mount | No   |
| Installation site          | ceiling, wall  |
| Installation               | Surface wiring, Wall   |
| Impact resistance          | IK03   |
| IP-rating                  | IP44   |
| Protection class           | I  |
| Ambient temperature        | from -20 up to 40 °C   |

| Cover material                | shrouds                |
|-------------------------------|------------------------|
| Luminous flux total product   | 6093 lm                |
| Measured luminos flux (360°)  | 6093 lm                |
| Total product efficiency      | 123 lm/W               |
| Colour temperature            | 3000 K                 |
| Colour variation LED          | SDCM3                  |
| Lamp                          | LED cannot be replaced |
| Service life LED L70B50 (25°) | > 36000 h              |
| LED cooling system            | Passive Thermo Control |
| Functions                     | Relay output           |
| Basic light level function    | No                     |
| Main light adjustable         | No                     |
| Twilight setting TEACH        | No                     |
| Interconnection               | Yes                    |
| Type of interconnection       | Master/slave           |
| Interconnection via           | Cable                  |
| Output                        | 49,4 W                 |
|                               |                        |

## LED floodlight without sensor - Professional Line

## **XLED PRO ONE Max**

without motion detector - anthracite EAN 4007841 069520 Article number 069520



## **Technical specifications**

| Housing material      | Aluminium                |
|-----------------------|--------------------------|
| Cover material        | Glass transparent        |
| Mains power supply    | 220 – 240 V / 50 – 60 Hz |
| Photo-cell controller | No                       |

| Colour Rendering Index CRI         | = 80                          |
|------------------------------------|-------------------------------|
| Product category                   | LED floodlight without sensor |
| Energieeffizienzklasse Lichtquelle | Е                             |

#### Accessories

| EAN 4007841 080983 | Surface mount adapter XLED PRO ONE Plus + Max |
|--------------------|---|
| EAN 4007841 079000 | RC 12   |


Subject to technical modifications

# **XLED PRO ONE Max**

without motion detector - anthracite EAN 4007841 069520 Article number 069520



## **Dimension Drawing**



## Slave circuit diagram

Subject to technical modifications



## Master/slave interconnection circuit diagram

