

Sensor-switched LED floodlight

# Spot Way SC

with motion detector & Bluetooth  
EAN 4007841 058661  
Article number 058661



LED

20.000 h

3000 K

3000K warm-white



38°



Infrared sensor 90°



max. 10 m



Twilight switch



IP44



Light source  
replaceable by end  
user



Control gear not  
exchangeable



2 - 1000 lux

## Function description

Timeless look. Quickly interconnected. The elegant, swivelling ground spotlight (57 cm) with 90° infrared sensor stylishly and brightly sets off driveways, garden parts etc. with 512 lm of warm-white light at 3000 K. Convenient interconnection, adjustment and control via free app. This makes child's play of selecting time and twilight settings, ON/OFF times as well as grouping lights. Includes mains plug (2.5 m) and lamp.

## Technical specifications

|                            |                                  |                               |  |
|----------------------------|----------------------------------|-------------------------------|--|
| Dimensions (L x W x H)     | 226 x 140 x 572 mm               | Reach, radial                 | r = 2 m (3 m <sup>2</sup> )                      |
| With lamp                  | Yes, LED lamp                    | Reach, tangential             | r = 10 m (79 m <sup>2</sup> )                    |
| With motion detector       | Yes                              | Photo-cell controller         | Yes  |
| Manufacturer's Warranty    | 3 years                          | Luminous flux total product   | 512 lm   |
| Settings via               | Bluetooth                        | Measured luminous flux (360°) | 512 lm   |
| Version                    | with motion detector & Bluetooth | Total product efficiency      | 64,8 lm/W  |
| PU1, EAN                   | 4007841058661                    | Colour temperature            | 3000 K   |
| Application, place         | Outdoors                         | Colour variation LED          | SDCM5  |
| Application, room          | outdoors, garden                 | Lamp                          | LED can be replaced                              |
| Colour                     | Anthracite                       | Service life LED L70B50 (25°) | > 20000 h  |
| Includes corner wall mount | No                               | Soft light start              | No   |
| Installation site          | Stand mounted                    | Continuous light              | selectable, 4h                                   |
| Installation               | Stand mounted                    | Functions                     | Manual ON / ON-OFF, Timer, Master/slave override |
| Impact resistance          | IK03                             | Twilight setting              | 2 – 2000 lx                                      |
| IP-rating                  | IP44                             | Time setting                  | 5 s – 60 Min.                                    |
| Protection class           | I                                | Basic light level function    | No   |
| Ambient temperature        | from -20 up to 40 °C             |                               |  |

<https://www.steinel.de>

Subject to technical modifications

01.2025 Page 1 from 2

Sensor-switched LED floodlight

# Spot Way SC

with motion detector & Bluetooth  
EAN 4007841 058661  
Article number 058661




## Technical specifications

|   |                          |
|---|--------------------------|
| Housing material                              | Aluminium                |
| Cover material                                | Plastic, transparent     |
| Mains power supply                            | 220 – 240 V / 50 – 60 Hz |
| Slave modeselectable                          | Yes                      |
| Sneak-by guard                                | No                       |
| Capability of masking out individual segments | No                       |
| Electronic scalability                        | No                       |
| Mechanical scalability                        | No                       |

|                            |                                |
|----------------------------|--------------------------------|
| Main light adjustable      | No                             |
| Twilight setting TEACH     | Yes                            |
| Interconnection            | Yes                            |
| Interconnection via        | Bluetooth                      |
| Output                     | 7,9 W                          |
| Colour Rendering Index CRI | = 81                           |
| Detection angle            | 90 °                           |
| Product category           | Sensor-switched LED floodlight |

## Detection Zone



Possible mounting height: -  
Orange: radial  
Black: tangential

## Dimension Drawing

