

Sensor-switched LED floodlight

Spot Way SC

with motion detector & Bluetooth
EAN 4007841 058661
Article number 058661



LED

20.000 h

3000 K

3000K warm-white



38°



Infrared sensor 90°



max. 10 m



Twilight switch



IP44



Light source
replaceable by end
user



Control gear not
exchangeable



2 - 1000 lux

Function description

Timeless look. Quickly interconnected. The elegant, swivelling ground spotlight (57 cm) with 90° infrared sensor stylishly and brightly sets off driveways, garden parts etc. with 512 lm of warm-white light at 3000 K. Convenient interconnection, adjustment and control via free app. This makes child's play of selecting time and twilight settings, ON/OFF times as well as grouping lights. Includes mains plug (2.5 m) and lamp.

Technical specifications

Dimensions (L x W x H)	226 x 140 x 572 mm	Reach, radial	r = 2 m (3 m ²)
With lamp	Yes, LED lamp	Reach, tangential	r = 10 m (79 m ²)
With motion detector	Yes	Photo-cell controller	Yes
Manufacturer's Warranty	3 years	Luminous flux total product	512 lm
Settings via	Bluetooth	Measured luminous flux (360°)	512 lm
Version	with motion detector & Bluetooth	Total product efficiency	64,8 lm/W
PU1, EAN	4007841058661	Colour temperature	3000 K
Application, place	Outdoors	Colour variation LED	SDCM5
Application, room	outdoors, garden	Lamp	LED can be replaced
Colour	Anthracite	Service life LED L70B50 (25°)	> 20000 h
Includes corner wall mount	No	Soft light start	No
Installation site	Stand mounted	Continuous light	selectable, 4h
Installation	Stand mounted	Functions	Manual ON / ON-OFF, Timer, Master/slave override
Impact resistance	IK03	Twilight setting	2 – 2000 lx
IP-rating	IP44	Time setting	5 s – 60 Min.
Protection class	I	Basic light level function	No
Ambient temperature	from -20 up to 40 °C		

<https://www.steinel.de>

Subject to technical modifications

05.2025 Page 1 from 2

Sensor-switched LED floodlight

Spot Way SC

with motion detector & Bluetooth
EAN 4007841 058661
Article number 058661



Technical specifications

Housing material	Aluminium
Cover material	Plastic, transparent
Mains power supply	220 – 240 V / 50 – 60 Hz
Slave modeselectable	Yes
Sneak-by guard	No
Capability of masking out individual segments	No
Electronic scalability	No
Mechanical scalability	No


Main light adjustable	No
Twilight setting TEACH	Yes
Interconnection	Yes
Interconnection via	Bluetooth
Output	7,9 W
Colour Rendering Index CRI	= 81
Detection angle	90 °
Product category	Sensor-switched LED floodlight

Accessories

EAN 4007841 088620

Wireless pushbutton TapDuo C

Detection Zone



Possible mounting height: -
Orange: radial
Black: tangential

Dimension Drawing

