

Sensor-switched LED floodlight

Spot Way SC

Sensor Connect

EAN 4007841 058661

Article number 058661



LED

20.000 h

3000 K

3000K
warm-white



38°



infrared sensor
90°



max. 10 m



Twilight switch



IP44



2 - 1000 lux



5 sec - 60 min



energy saving

Function description

Timeless look. Quickly interconnected. The elegant, swivelling ground spotlight (57 cm) with 90° infrared sensor stylishly and brightly sets off driveways, garden parts etc. with 512 lm of warm-white light at 3000 K. Convenient interconnection, adjustment and control via free app. This makes child's play of selecting time and twilight settings, ON/OFF times as well as grouping lights. Includes mains plug (2.5 m) and lamp.

Spot Way SC

Sensor Connect

EAN 4007841 058661


Article number 058661

Technical specifications

Dimensions (L x W x H)	226 x 140 x 572 mm
Mains power supply	220 – 240 V / 50 – 60 Hz
Sensor Technology	passive infrared
Output	7,9 W
Interconnection	Yes
Interconnection via	Bluetooth
Slave modeselectable	Yes
Luminous flux total product	512 lm
Total product efficiency	64,8 lm/W
Measured luminous flux (360°)	512 lm
Colour temperature	3000 K
Colour variation LED	SDCM5
Colour Rendering Index	80-89
With lamp	Yes, LED lamp
Lamp	LED can be replaced
Base	GU10
With motion detector	Yes
Detection angle	90 °
Angle of aperture	90 °
Capability of masking out individual segments	No
Electronic scalability	No
Mechanical scalability	No

Reach, radial	r = 2 m (3 m ²)
Reach, tangential	r = 10 m (79 m ²)
Continuous light	selectable, 4h
Photo-cell controller	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Basic light level function	No
Main light adjustable	No
Functions	Timer, Master/slave override
Soft light start	No
Impact resistance	IK03
IP-rating	IP44
Protection class	I
Ambient temperature	-20 – 40 °C
Housing material	Aluminium
Cover material	Plastic, transparent
Manufacturer's Warranty	3 years
Settings via	Bluetooth
Installation site	Stand
Version	Sensor Connect
PU1, EAN	4007841058661

Detection Zone



Mögliche Montagehöhe: –
 Orange: radial
 Schwarz: tangential

Dimension Drawing

