Sensor-switched outdoor light

L 12 S Anthracite EAN 4007841 657819 Article number 657819







Function description

Looks really good, pricewise too. Designer sensor-switched outdoor light L 12 S, ideal for building entrances and building fronts, 180° angle of coverage, reach up to 10 m, selectable time and twilight threshold, sensor tilts through 90° for exact adjustment of the detection zone, aluminium trim panel.

Technical specifications

Dimensions (L x W x H)	108 x 155 x 272 mm	Slave modeselectable	No
With lamp	No	Sneak-by guard	Yes
Manufacturer's Warranty	3 years	Capability of masking out individual Yes	
Settings via	Potentiometers	-	No
With remote control	No	Electronic scalability	
Version	Anthracite	Mechanical scalability	No
	4007841657819	Reach, radial	$r = 3 m (14 m^2)$
PU1, EAN		Reach, tangential	r = 10 m (157 m ²)
Application, place	Outdoors	Photo-cell controller	Yes
Application, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway	Cover material	sticker
		Lamp	All-purpose lamp
Installation site	wall	Base	E27
Impact resistance	IK03	Soft light start	No
IP-rating	IP44	Twilight setting	2 – 2000 lx
Protection class	II	Time setting	8 s – 35 Min.
Ambient temperature	from -20 up to 40 °C	Basic light level function	No
Housing material	Aluminium	Interconnection	No
Cover material	Plastic, opal	Optimum mounting height	2 m

Page 1 from 2

05.2025

Sensor-switched outdoor light


L 12 S Anthracite EAN 4007841 657819 .- steinel

Technical specifications

Article number 657819

Mains power supply	230 – 240 V / 50 Hz	Detection angle	180 °
Output	60 W	Product category	Sensor-switched outdoor light
Power consumption	0,55 W		
Mounting height max.	3,00 m		


Detection Zone



Possible mounting height: 1,80 m - 3,00 m Orange: radial Black: tangential

Circuit diagram

Dimension Drawing



Subject to technical modifications