


Outdoor light without sensor

L 800 C

Anthracite

EAN 4007841 079291

Article number 079291



Downlight

3000 K

3000K warm-white



20 - 50% basic
brightness



IP44



connectable via
bluetooth



Settings via App



Light source not
exchangeable



Control gear not
exchangeable



outdoor light

3 years

manufacturer's
warranty steinel.de/
garantie

Function description

Elegant and clear. The L 800 C downlight without sensor is an exceptionally elegant LED outdoor light. It is a marriage between sophisticated product design and high-quality aluminium. Warm white light (3,000 K) with 466 lm at 7,5 W ensures an inviting lighting mood. It can be interconnected with the sensor version in a flash via Bluetooth, or alternatively can be used as an elegant stand-alone solution.

Technical specifications

Dimensions (L x W x H)	146 x 230 x 88 mm
With lamp	Yes, STEINEL LED system
Manufacturer's Warranty	3 years
Settings via	App, Bluetooth
With remote control	No
Version	Anthracite
PU1, EAN	4007841079291
Application, place	Outdoors
Application, room	garden, front door, courtyard & driveway, all round the building, terrace / balcony
Colour	Anthracite
includes sheet of self-adhesive numbers	No
Package content	1
Installation site	wall
Impact resistance	IK03
IP-rating	IP44

Photo-cell controller	No
Transmitter power	< 1 mW
Luminous flux total product	466 lm
Measured luminous flux (360°)	466 lm
Total product efficiency	62 lm/W
Colour temperature	3000 K
Lamp	LED cannot be replaced
Service life LED L70B50 (25°)	> 60000 h
Base	without
LED cooling system	Active and Passive Thermo Control
Soft light start	Yes
Basic light level function	Yes
Basic light level function, detail	only in combination with the SC version
Interconnection	Yes
Basic light level function in per cent	10 – 100 %
Basic light level function percentage, from	10 %

<https://www.steinel.de>

Subject to technical modifications

09.2026 Page 1 from 3

Outdoor light without sensor

L 800 C

Anthracite

EAN 4007841 079291

Article number 079291



Technical specifications

Protection class	II
Ambient temperature	from -20 up to 40 °C
Housing material	Aluminium
Cover material	Plastic, opal
Mains power supply	220 – 240 V / 50 – 60 Hz
Output	7,5 W
Mounting height max.	2,50 m

Basic light level function percentage, up to	100 %
Interconnection via	Bluetooth
Colour Rendering Index CRI	= 82
Optimum mounting height	2 m
Product category	Outdoor light without sensor

Accessories

EAN 4007841 088620

Wireless pushbutton TapDuo C

Outdoor light without sensor

L 800 C


Anthracite

EAN 4007841 079291

Article number 079291




Detection Zone



Possible mounting height: 1,80 m – 2,50 m
Orange: radial and tangential

Dimension Drawing



Circuit diagram Bluetooth

