LED floodlight without sensor

XLED home 2

V2 black EAN 4007841 033118 Article number 033118







3000 K



IP44















30 years (Ø 4,5h / day)

3000K warm-white

180° horizontal 180° vertikal

manufacturer's warranty steinel.de/ garantie

Control gear not exchangeable

CE

Function description

Dazzlingly stylish LED floodlight. XLED home 2 – the outdoor floodlight without sensor. Freely swivelling LED panel with new opal cover for pleasant wide-area lighting (1550 lm at 13,7 W). Swivelling range: 180° (horizontally and vertically). Cooling system of high thermal conductivity magnesium composite (HCMC).

Technical specifications

Dimensions (L x W x H)	161 x 180 x 181 mm
With lamp	Yes, STEINEL LED system
With motion detector	No
Manufacturer's Warranty	5 years
Version	black
PU1, EAN	4007841033118
Application, place	Outdoors
Application, room	outdoors, all round the building, terrace / balcony, courtyard & driveway
Installation site	wall, corner
Installation	Surface wiring, corner, Wall
Impact resistance	IK03
IP-rating	IP44
Protection class	
Ambient temperature	from -20 up to 40 °C
Housing material	HCMC
Cover material	Plastic, opal

Mains power supply	220 – 240 V / 50 – 60 Hz
Photo-cell controller	No
Luminous flux total product	1550 lm
Measured luminos flux (360°)	1550 lm
Total product efficiency	113 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Service life LED L70B50 (25°)	> 60000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	HCMC (High Conductive Magnesium Composite)
Output	13,7 W
Colour Rendering Index CRI	= 82
Product category	LED floodlight without sensor
Energieeffizienzklasse Lichtquelle	Е

LED floodlight without sensor

XLED home 2


V2 black EAN 4007841 033118 Article number 033118




Accessories

EAN 4007841 055875	Corner wall mount XLED home 2/ PRO 240
EAN 4007841 053086	Corner wall mount XLED Home 2/ Pro 240
EAN 4007841 055615	Corner wall mount XLED home 2/ PRO 240

Dimension Drawing



Light Distribution Curve



Slave circuit diagram

