











# PD-8 ECO

COM1 - in-ceiling installation white  
EAN 4007841 087913  
Article number 087913



									
Magnet zur einfachen Installation	Infrarot-Sensor 360°	Montagehöhe max. 4 m	Präsenz Ø 6 m	Max. 8 m	2 - 1000 Lux	IP20	Teach mode	Herstellergarantie steinel-professional.de/garantie	CE

## Function description

Motion detection, presence detection and light measurement for offices, meeting rooms, passageways and more – the 360° IR presence detectors are sensNORM-compliant and ideal for sensor-based standard requirements in public buildings. With COM1, KNX and DALI-2 IPD interface. With COM1 interface, key input and fully/semi-automatic mode. Motion detection range: Ø 8 or Ø 24 m. Presence detector function with Ø 6 or Ø 7.5 m detection zone. Includes insertable cover caps in a matching colour. For concealed wiring, surface mounting and recessed ceiling installation. Configuration and operation via Smart Remote control or potentiometer. Installation-friendly modular magnetic plug-in connection. LED feedback for safe commissioning. Mounting height max. 4 m. Parallel switching (up to 10 sensors). Switching output: 2000 watt or 500 watt (LED). In black or white.

# PD-8 ECO

COM1 - in-ceiling installation white  
 EAN 4007841 087913  
 Article number 087913



## Technical specifications

Dimensions (Ø x H)	109 x 109 mm
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	Remote control, Smart Remote, Potentiometers
With remote control	No
Version	COM1 - in-ceiling installation white
PU1, EAN	4007841087913
Type	Motion and Presence Detector
Application, place	Indoors
Application, room	one-person office, function room / ancillary room, Indoors, warehouse
Colour	white
Includes corner wall mount	No
Installation site	ceiling
Installation	In-ceiling installation, Ceiling
IP-rating	IP20
Ambient temperature	-20 – 50 °C
Material	Plastic
Switching output 1, resistive	2000 W
Switching output 1, number of LEDs / fluorescent lamps	50 pcs.
LED lamps > 8 W	500 W
Capacitive load in µF	176 µF
Technology, sensors	passive infrared, Light sensor


Mounting height	2 – 4 m
Mounting height max.	4,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Capability of masking out individual segments	Yes
Electronic scalability	No
Mechanical scalability	No
Reach, radial	Ø 4.5 m (16 m <sup>2</sup> )
Reach, tangential	Ø 8 m (50 m <sup>2</sup> )
Reach, presence	Ø 6 m (28 m <sup>2</sup> )
Switching zones	492 switching zones
Cover material	shrouds
Functions	Motions sensor, Light sensor, Presence function, Presence detector logic, Semi-/fully automatic, Potentiometer, Relay output, Normal / test mode
Twilight setting	2 – 1000 lx
Time setting	5 s – 60 Min.
Main light adjustable	No
Twilight setting TEACH	Yes
Constant-lighting control	No
Type of interconnection	Master/master
Interconnection via	Cable
Interconnection, number	max. 10 sensors

# PD-8 ECO


COM1 - in-ceiling installation white  
EAN 4007841 087913  
Article number 087913




**Detection Zone 1**




**Detection Zone 2**



**Dimension Drawing 1**



**Dimension Drawing 2**




# PD-8 ECO

COM1 - in-ceiling installation white  
EAN 4007841 087913  
Article number 087913



## Circuit diagram



## Circuit diagram for interconnecting several sensors

