


Sensor-switched LED outdoor light

L 810 SC

Silver

EAN 4007841 087562

Article number 087562



Up-/Downlight

3000 K

3000K warm-white



intelligent high
frequency sensor
160°



1 - 5 m



IP44



2 - 2000 lux



Light source not
exchangeable



Control gear not
exchangeable



5 sec - 60 min



soft light start

Function description

The most modern outdoor light in the world. Designer sensor-switched outdoor light L 810 SC with invisible high-frequency sensor, ideal for building entrances and fronts of buildings, 9,8 W STEINEL LED lighting system, 679 lm, 160° coverage angle, reach from 1 - 5 m, for stylish up and downlighting, includes night light function, dimmable main light, elegant soft light start, permanent light and schedule function. Wirelessly networkable via Bluetooth Mesh and adjustable and controllable via free app.

Technical specifications

Dimensions (L x W x H)	145 x 230 x 88 mm
With lamp	Yes, STEINEL LED system
Manufacturer's Warranty	3 years
Settings via	App, Bluetooth Mesh
With remote control	No
Version	Silver
PU1, EAN	4007841087562
Application, place	Outdoors
Application, room	garden, front door, courtyard & driveway, all round the building, terrace / balcony
Colour	Silver
includes sheet of self-adhesive numbers	No
Package content	1
Installation site	wall
Impact resistance	IK03

Photo-cell controller	Yes
Transmitter range	30 m
Transmitter power	< 1 mW
Luminous flux total product	679 lm
Measured luminous flux (360°)	679 lm
Total product efficiency	69 lm/W
Colour temperature	3000 K
Lamp	LED cannot be replaced
Service life LED L70B50 (25°)	> 60000 h
Base	without
LED cooling system	Active and Passive Thermo Control
Soft light start	Yes
Continuous light	selectable
Functions	Motions sensor
Twilight setting	2 - 2000 lx
Time setting	5 s - 60 Min.

<https://www.steinel.de>

Subject to technical modifications

09.2026 Page 1 from 3

L 810 SC

Silver
EAN 4007841 087562
Article number 087562



Technical specifications

IP-rating	IP44
Protection class	II
Ambient temperature	from -20 up to 40 °C
Housing material	Aluminium
Cover material	Plastic, opal
Mains power supply	220 – 240 V / 50 – 60 Hz
Output	9,8 W
Mounting height max.	2,50 m
Slave modeselectable	Yes
Sneak-by guard	No
Capability of masking out individual segments	No
Electronic scalability	Yes
Mechanical scalability	No
Reach, detail	Detection zone adjustable on 2 axes
Reach, radial	r = 5 m (35 m ²)
Reach, tangential	r = 5 m (35 m ²)

Basic light level function	Yes
Basic light level function time	OFF, Brightness-controlled, 10 sec – 60 min
Main light adjustable	10 - 100 %
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Basic light level function in per cent	10 – 100 %
Basic light level function percentage, from	10 %
Basic light level function percentage, up to	100 %
Interconnection via	Bluetooth Mesh
Colour Rendering Index CRI	= 82
Optimum mounting height	2 m
Detection angle	160 °
Product category	Sensor-switched LED outdoor light

Accessories

EAN 4007841 088620

Wireless pushbutton TapDuo C

Sensor-switched LED outdoor light

L 810 SC


Silver

EAN 4007841 087562

Article number 087562




Detection Zone



Possible mounting height: 1,80 m – 2,50 m

Orange: radial and tangential

Dimension Drawing



Circuit diagram Bluetooth

