

Sensor-switched LED outdoor light

My L 270 digi SC

with motion detector & Bluetooth
EAN 4007841 085940
Article number 085940



LED

3000 K



Infrarot-Sensor
180°



3 individuell
einstellbare Zonen



Max. 8 m



IP44



2 - 2000 Lux (via
App)



Lichtquelle nicht
austauschbar



Betriebsgerät nicht
austauschbar



5 Sek - 60 Min (via
App)

Function description

Digital revolution. LED outdoor light L 270 digi SC (including house number panel) from the STEINEL Connect series. With revolutionary digi-sensor technology, 8 m detection radius and 3 detection zones. Interconnectable via Bluetooth. Adjustable via app. 637 lm, 7,8 W, 3000 K. With basic light level and soft light start function. The stay-ON time can be digitally selected (10 seconds to 60 minutes). In high-quality aluminium.

Technical specifications

Dimensions (L x W x H)	65 x 366 x 235 mm
With lamp	Yes, STEINEL LED system
Manufacturer's Warranty	3 years
Settings via	App, Smartphone, Tablet, Connect Bluetooth Mesh
With remote control	No
Version	with motion detector & Bluetooth
PU1, EAN	4007841085940
Application, place	Outdoors
Application, room	outdoors, front door
Colour	Anthracite
includes sheet of self-adhesive numbers	No
Installation site	wall
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-10 – 40 °C

Reach, detail	3 detection zones can be (de)activated individually, range can be set separately
Reach, radial	r = 6 m (57 m ²)
Reach, tangential	r = 8 m (101 m ²)
Luminous flux total product	637 lm
Measured luminous flux (360°)	637 lm
Colour temperature	3000 K
Lamp	LED cannot be replaced
Service life LED L70B50 (25°)	> 60000 h
Soft light start	Yes
Continuous light	selectable
Twilight setting	2 – 2000 lx
Time setting	10 s – 60 Min.
Basic light level function	Yes
Basic light level function, detail	LED effect light
Basic light level function time	10s-60 min, OFF, Brightness-controlled

<https://www.steinell.de>

Subject to technical modifications

04.2024 Page 1 from 2

Sensor-switched LED outdoor light

My L 270 digi SC

with motion detector & Bluetooth
EAN 4007841 085940
Article number 085940




Technical specifications

Housing material	Aluminium
Mains power supply	220 – 240 V / 50 – 60 Hz
Output	7,8 W
Average rated life expectancy of power supply unit at 25°C	> 60000 h
Mounting height max.	2,50 m
Slave modeselectable	Yes
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	Yes
Mechanical scalability	No

Main light adjustable	10 - 100 %
Twilight setting TEACH	Yes
Interconnection	Yes
Basic light level function in per cent	10 – 100 %
Basic light level function percentage, from	10 %
Basic light level function percentage, up to	100 %
Interconnection via	Bluetooth Mesh Connect
Colour Rendering Index CRI	= 82
Optimum mounting height	2 m
Detection angle	180 °

Dimension Drawing



Circuit diagram Bluetooth

