

RS PRO A10 SC

warm white anthracite
 EAN 4007841 085315
 Article number 085315



LED

36 years (Ø 4,5h / day)



Settings via App

3000 K

3000K warm-white



high frequency sensor 360°



max. 8 m



2 - 2000 lux




IP54



shock proof IK10



Light source not exchangeable



Control gear not exchangeable

Function description

Elegant and robust. Sophisticated design for demanding environments: Equipped with a powerful high-frequency sensor and an aluminium chassis that is as attractive as it is robust, the A series is ideal for pergolas or similar applications thanks to its IK10 impact resistance and tested IP54 protection class. In combination with our Connected Lighting System, the luminaires can be controlled using a wireless push-button. Semi-automatic operation, timer functions, the setting of neighbour groups and tracking light can also be implemented quickly and easily using Connected Lighting. Of course, cross-series networking is also possible at any time without any problems. Connection to central battery systems possible.

Technical specifications

Dimensions (Ø x H)	193 x 69 mm	Photo-cell controller	Yes
With lamp	Yes, STEINEL LED system	Transmitter power	< 1 mW
With motion detector	Yes	Luminous flux total product	1095 lm
Manufacturer's Warranty	5 years	Total product efficiency	102,3 lm/W
Settings via	Bluetooth, App	Colour temperature	3000 K
With remote control	No	Colour variation LED	SDCM3
Version	warm white anthracite	Lamp	LED cannot be replaced
PU1, EAN	4007841085315	Base	without
Application, place	Indoors	LED cooling system	Passive Thermo Control
Application, room	corridor / aisle, function room / ancillary room, warehouse, kitchenette, stairwell, changing room, WC / washroom	Soft light start	Yes
Colour	Anthracite	Continuous light	selectable
includes sheet of self-adhesive numbers	No	Functions	Connection to central battery systems, Selecting programmed lighting scenarios, Motions sensor, DIM function, Adjustable fade time when switching on and off, Semi-/ fully automatic, Neighbouring group
Installation site	ceiling, wall		


RS PRO A10 SC

warm white anthracite
 EAN 4007841 085315
 Article number 085315

Technical specifications

Installation	Surface wiring, Ceiling	function, Encrypted communication, Timer
Impact resistance	IK10	Twilight setting
IP-rating	IP54	2 – 2000 lx
Protection class	II	Time setting
Ambient temperature	from -20 up to 40 °C	10 s – 60 Min.
Housing material	Aluminium	Basic light level function
Cover material	PC, opal	Yes
Mains power supply	220 – 240 V / 50 – 60 Hz	Basic light level function time
Mounting height max.	4,00 m	1-60 min
HF-system	5,8 GHz	Main light adjustable
Slave mode/selectable	Yes	0 - 100 %
Detection	also through glass, wood and stud walls	Twilight setting TEACH
Capability of masking out individual segments	No	Yes
Electronic scalability	Yes	Interconnection
Mechanical scalability	No	Yes
Reach, radial	Ø 8 m (50 m ²)	Type of interconnection
Reach, tangential	Ø 8 m (50 m ²)	Master/master
		Interconnection via
		Bluetooth Mesh Connect
		Lifetime LED according to IEC-62717 (L70)
		> 60.000 Std.
		Basic light level function in per cent
		0 – 100 %
		Output
		10,7 W
		Colour Rendering Index CRI
		= 80
		Angle of aperture
		160 °
		IP-rating, ceiling
		IP54
		Detection angle
		360 °
		Product category
		Sensor-switched LED indoor light

Detection Zone



Possible mounting height: 2,00 m – 4,00 m
 Orange: radial and tangential

Dimension Drawing

