

Sensor-switched LED indoor light - Professional Line

RS PRO A30 SC

warm white anthracite
EAN 4007841 085353
Article number 085353



LED

36 years (Ø 4,5h / day)



Settings via App

3000 K

3000K warm-white



high frequency sensor 360°



max. 8 m



IP54



shock proof IK10



2 - 2000 lux



Light source not exchangeable



Control gear not exchangeable

Function description

Elegant and robust. Sophisticated design for demanding environments: Equipped with a powerful high-frequency sensor and an aluminium chassis that is as attractive as it is robust, the A series is ideal for pergolas or similar applications thanks to its IK10 impact resistance and tested IP54 protection class. In combination with our Connected Lighting System, the luminaires can be controlled using a wireless push-button. Semi-automatic operation, timer functions, the setting of neighbour groups and tracking light can also be implemented quickly and easily using Connected Lighting. Of course, cross-series networking is also possible at any time without any problems. Connection to central battery systems possible.

Technical specifications

Dimensions (Ø x H)	331 x 69 mm
With lamp	Yes, STEINEL LED system
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	Bluetooth, App
With remote control	No
Version	warm white anthracite
PU1, EAN	4007841085353
Application, place	Indoors
Application, room	corridor / aisle, function room / ancillary room, warehouse, kitchenette, stairwell, changing room, WC / washroom
Colour	Anthracite
includes sheet of self-adhesive numbers	No
Installation site	ceiling, wall

Photo-cell controller	Yes
Transmitter power	< 1 mW
Luminous flux total product	2534 lm
Total product efficiency	122,4 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
Lamp	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
Continuous light	selectable
Functions	Connection to central battery systems, Selecting programmed lighting scenarios, Motions sensor, DIM function, Adjustable fade time when switching on and off, Semi-/ fully automatic, Neighbouring group

<https://www.steinel.de>

Subject to technical modifications

01.2025 Page 1 from 2

RS PRO A30 SC


warm white anthracite
EAN 4007841 085353
Article number 085353



Technical specifications

Installation	Surface wiring, Ceiling		function, Encrypted communication, Timer
Impact resistance	IK10	Twilight setting	2 – 2000 lx
IP-rating	IP54	Time setting	10 s – 60 Min.
Protection class	II	Basic light level function	Yes
Ambient temperature	from -20 up to 40 °C	Basic light level function time	1-60 min
Housing material	Aluminium	Main light adjustable	0 - 100 %
Cover material	PC, opal	Twilight setting TEACH	Yes
Mains power supply	220 – 240 V / 50 – 60 Hz	Interconnection	Yes
Mounting height max.	4,00 m	Type of interconnection	Master/master
HF-system	5,8 GHz	Interconnection via	Bluetooth Mesh Connect
Slave modeselectable	Yes	Lifetime LED according to IEC-62717 (L70)	> 60.000 Std.
Detection	also through glass, wood and stud walls	Basic light level function in per cent	0 – 100 %
Capability of masking out individual segments	No	Output	20,7 W
Electronic scalability	Yes	Colour Rendering Index CRI	= 80
Mechanical scalability	No	Angle of aperture	160 °
Reach, radial	Ø 8 m (50 m²)	IP-rating, ceiling	IP54
Reach, tangential	Ø 8 m (50 m²)	Detection angle	360 °
		Product category	Sensor-switched LED indoor light

Detection Zone



Possible mounting height: 2,00 m – 4,00 m
Orange: radial and tangential

Dimension Drawing

