

TCL PRO

white

EAN 4007841 089146

Article number 089146



15 lux



IP54



connectable via bluetooth



CE

Function description

The safeguard for time-based automation. This timer never runs out of time thanks to the Real Time Clock. One year always has 31,536,000 seconds. A 7-day battery buffer ensures that the system continues to run smoothly even in the event of a power failure. The TCL PRO has a light sensor and can transmit the lux values to the system via Bluetooth Mesh. A perfect network sensor for safeguarding time-based automation.

Technical specifications

Dimensions (L x W x H)	38 x 95 x 95 mm
With motion detector	No
Manufacturer's Warranty	5 years
Settings via	Bluetooth Mesh, App, Smartphone
With remote control	No
Version	white
PU1, EAN	4007841089146
Type	Photo-cell controller
Application, place	Outdoors
Application, room	outdoors, front door, courtyard & driveway, Indoors, all round the building, terrace / balcony
Colour	white
Colour, RAL	9003
Installation site	wall
Installation	Surface wiring, Wall
IP-rating	IP54
Ambient temperature	from -20 up to 40 °C

Material	Plastic
Mains power supply	220 – 240 V / 50 – 60 Hz
Power consumption	0,5 W
Technology, sensors	Other
Mounting height	1,80 – 4,00 m
Mounting height max.	4,00 m
Optimum mounting height	2 m
Twilight setting	1 – 1000 lx
Basic light level function	No
Twilight setting TEACH	Yes
Constant-lighting control	No
Interconnection	Yes
Type of interconnection	Master/master, Master/slave
Interconnection via	Bluetooth Mesh
Product category	Light sensor

Light sensor - Professional Line

TCL PRO

white

EAN 4007841 089146

Article number 089146



Dimension Drawing

