Motion detector - Professional Line

MD IR N360

COM1 - in-ceiling installation white EAN 4007841 080587 Article number 080587

















Function description

Perfect sensor solution for entrances and façades. The powerful, LED-compatible (600 W) MD IR N360 with 360° detection range for ceiling mounting and extended Eagle Eye detection for frontal movement and convenient control and networking via Bluetooth Mesh. Including smart Connect functions for networking luminaires, timer programmes and wireless push-buttons.

Technical specifications

Dimensions (Ø x H)	83 x 74 mm	Technology, sensors	
With motion detector	Yes	Mounting height	
Manufacturer's Warranty	5 years	Mounting height max.	
Settings via	Bluetooth, Smartphone, Tablet	Optimum mounting heigh	
With remote control	No	Detection angle	
Version	COM1 - in-ceiling installation white	Sneak-by guard	
PU1, EAN	4007841080587	Capability of masking out	
Туре	Motion detectors	segments	
Application, place	Outdoors, Indoors	Electronic scalability	
Application, room	front door, courtyard & driveway, all round the building, terrace / balcony, Indoors, outdoors	Mechanical scalability	
		Reach, radial	
		Reach, tangential	
Colour	white	Cover material	
Includes corner wall mount	No		
Installation site	corner, wall	Functions	
Installation	Ceiling, In-ceiling installation	Twilight setting	
IP-rating	IP54	Time setting	
Protection class	II	Basic light level function	

passive infrared, Light sensor
1,80 – 6,00 m
6,00 m
2 m
360 °
Yes
Yes
Yes
No
Ø 7 m (38 m²)
Ø 26 m (531 m ²)
shrouds
Motions sensor, Light sensor, Relay output, Data monitoring
2 – 2000 lx
5 s – 60 Min.
No

https://www.steinel.de

Subject to technical modifications

05.2025 Page 1 from 2

MD IR N360

COM1 - in-ceiling installation white EAN 4007841 080587 Article number 080587




Technical specifications

Ambient temperature	from -20 up to 40 °C
Material	Plastic
Mains power supply	220 – 240 V / 50 – 60 Hz
Switching output 1, resistive	2000 W
Switching output 1, number of LEDs / fluorescent lamps	10 pcs.
Power consumption	0,3 W

Twilight setting TEACH	Yes
Constant-lighting control	No
Interconnection	Yes
Interconnection via	Bluetooth
Reichweite Radial Eagle Eye max.	6 m
Product category	Motion detector

Detection Zone



Possible mounting height: 1,80 m – 6,00 m Orange: radial Black: tangential

Dimension Drawing

