

Hallway

COM1 - concealed black
EAN 4007841 086336
Article number 086336



max. 25 x 3 m

2000 W

max. 2000 W



IP20



5 sec - 60 min



2 - 12 m

iQ

IQ-mode



connectable via
bluetooth

5 years

manufacturer's
warranty steinel.de/
garantie



CE

Function description

The cleverer hallway sensor knows more. Perfect radial detection up to 25 m – ideal for long corridors and hallways. Reach can be adjusted in both directions. Contemporary Control PRO II design. Featuring Bluetooth technology. Interfaces for COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave). Light measurement is not possible with the black sensors. An external light meter must be integrated via Bluetooth or KNX for this purpose.

Technical specifications

Dimensions (L x W x H)	67 x 103 x 103 mm
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	Bluetooth Mesh
With remote control	No
Version	COM1 - concealed black
PU1, EAN	4007841086336
Type	Presence detector
Application, place	Indoors
Application, room	Indoors, corridor / aisle
Colour	black
Colour, RAL	9005
Includes corner wall mount	No
Installation site	ceiling
Installation	Concealed wiring, Ceiling
IP-rating	IP20
Ambient temperature	from -20 up to 50 °C

Mounting height	2 – 4 m
Mounting height max.	4,00 m
Optimum mounting height	2,8 m
HF-system	5,8 GHz
Detection	also through glass, wood and stud walls
Detection angle	Aisle, 360 °
Angle of aperture	160 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	25 x 3 m (75 m ²)
Reach, tangential	25 x 3 m (75 m ²)
Transmitter power	< 1 mW
Functions	Group parameterisation, Semi-/fully automatic, Lighting scenario, Manual

Hallway

COM1 - concealed black
EAN 4007841 086336
Article number 086336



Technical specifications

Technical specifications

Material	Plastic	ON / ON-OFF, Neighbouring group function, Normal / test mode
Mains power supply	220 – 240 V / 50 – 60 Hz	Twilight setting
Switching output 1, resistive	2000 W	Time setting
Switching output 1, number of LEDs / fluorescent lamps	8 pcs.	Basic light level function
Switching output 1, floating	No	Main light adjustable
Switching output 1, low-voltage halogen lamps	2000 VA	Twilight setting TEACH
Power consumption	1 W	Constant-lighting control
Technology, sensors	High frequency	Interconnection
		Interconnection via
		Product category

Hallway

COM1 - concealed black
EAN 4007841 086336
Article number 086336

Detection Zone



Possible mounting height: 2,00 m – 4,00 m
Orange: radial and tangential

Dimension Drawing



Master circuit diagram

