


24V-Garden LED globe light

Sphera C 24V

300 mm

EAN 4007841 089368

Article number 089368



outdoor globe light



Plug & Play - easy to install



Low-voltage system



Bluetooth Mesh



Settings via App



IP65



Light source not exchangeable



CE

3 years

manufacturer's warranty steinel.de/garantie

Function description

The globe light for stylish lighting accents in outdoor areas. As part of the 24V garden lighting system, the "Sphera C 24V 300 mm" with its harmonious round shape blends elegantly into any garden design. It shines in either warm white or colored light, providing atmospheric lighting with 529 lm light output at a low 5,04 W consumption. The light automatically turns on at dusk and off at dawn – alternatively, it can be controlled via app with programmable on and off times. Power supply and cables are not included.

Technical specifications

With lamp	Yes, STEINEL LED system
Manufacturer's Warranty	3 years
Settings via	Bluetooth Mesh
With remote control	No
Version	300 mm
PU1, EAN	4007841089368
Application, place	Outdoors
Application, room	outdoors, garden, terrace / balcony
Colour	Anthracite
includes sheet of self-adhesive numbers	No
Package content	1
Installation site	Floor
Impact resistance	IK07
IP-rating	IP65
Ambient temperature	from -20 up to 40 °C
Housing material	Plastic

Luminous flux total product	529 lm
Measured luminous flux (360°)	529 lm
Colour temperature	all colors + 1800-4000 K
Colour variation LED	SDCM3
Lamp	LED cannot be replaced
Service life LED L70B50 (25°)	> 60000 h
Continuous light	selectable
Twilight setting	2 – 2000 lx
Main light adjustable	10 - 100 %
Twilight setting TEACH	Yes
Interconnection	Yes
Interconnection via	Bluetooth Mesh
Colour Rendering Index CRI	= 84
R9-Farb wiedergabeindex	11
Product category	24V-Garden LED globe light
Ausführung des Betriebsgeräts	with twilight switch

<https://www.steinel.de>

Subject to technical modifications

02.2026 Page 1 from 2

24V-Garden LED globe light

Sphera C 24V

300 mm

EAN 4007841 089368

Article number 089368



Technical specifications

Cover material	Plastic, structured
Output	5,04 W
Average rated life expectancy of power supply unit at 25°C	> 60000 h
Photo-cell controller	Yes

Anzahl der Ausgänge	1
Geeignet für Konstantspannung	Yes
Geeignet für Konstantstrom	No
Cord length	0.65 m

Accessories

EAN 4007841 088620	Wireless pushbutton TapDuo C
EAN 4007841 089290	Cable 24V
EAN 4007841 089276	Cable 24V
EAN 4007841 089283	Cable 24V
EAN 4007841 089269	Power Supply 24V
EAN 4007841 089252	Power Supply 24V
EAN 4007841 091491	Aluminium ground spike 24V
EAN 4007841 089313	Cross Connector 24V
EAN 4007841 089306	T-Connector 24V

Dimension Drawing

