

24V-Garden LED globe light

# Sphera C 24V

300 mm

EAN 4007841 089368

Article number 089368



outdoor globe light




Plug & Play - easy to install



Low-voltage system




Bluetooth Mesh



Settings via App



IP65



Light source not exchangeable



CE



3 years  
manufacturer's warranty steinel.de/  
garantie

## Function description

The globe light for stylish lighting accents in outdoor areas. As part of the 24V garden lighting system, the "Sphera C 24V 300 mm" with its harmonious round shape blends elegantly into any garden design. It shines in either warm white or colored light, providing atmospheric lighting with 529 lm light output at a low 5,04 W consumption. The light automatically turns on at dusk and off at dawn – alternatively, it can be controlled via app with programmable on and off times. Power supply and cables are not included.

## Technical specifications

With lamp	Yes, STEINEL LED system	Luminous flux total product	529 lm
Manufacturer's Warranty	3 years	Measured luminous flux (360°)	529 lm
Settings via	Bluetooth Mesh	Colour temperature	all colors + 1800-4000 K
With remote control	No	Colour variation LED	SDCM3
Version	300 mm	Lamp	LED cannot be replaced
PU1, EAN	4007841089368	Service life LED L70B50 (25°)	> 60000 h
Application, place	Outdoors	Continuous light	selectable
Application, room	outdoors, garden, terrace / balcony	Twilight setting	2 – 2000 lx
Colour	Anthracite	Main light adjustable	10 - 100 %
includes sheet of self-adhesive numbers	No	Twilight setting TEACH	Yes
Package content	1	Interconnection	Yes
Installation site	Floor	Interconnection via	Bluetooth Mesh
Impact resistance	IK07	Colour Rendering Index CRI	= 84
IP-rating	IP65	R9-Farbwideregabeindex	11
Protection class	III	Product category	24V-Garden LED globe light
Ambient temperature	from -20 up to 40 °C	Ausführung des Betriebsgeräts	with twilight switch

<https://www.steinel.de>

Subject to technical modifications

04.2026 Page 1 from 2

24V-Garden LED globe light

# Sphera C 24V

300 mm

EAN 4007841 089368

Article number 089368



## Technical specifications

Housing material	Plastic
Cover material	Plastic, structured
Output	5,04 W
Average rated life expectancy of power supply unit at 25°C	> 60000 h
Photo-cell controller	Yes

Anzahl der Ausgänge	1
Geeignet für Konstantspannung	Yes
Geeignet für Konstantstrom	No
Cord length	0.65 m

## Accessories

EAN 4007841 088620	Wireless pushbutton TapDuo C
EAN 4007841 089290	Cable 24V 5m
EAN 4007841 089276	Cable 24V 1m
EAN 4007841 089283	Cable 24V 2,5m
EAN 4007841 089269	Power Supply 24V 100 W
EAN 4007841 089252	Power Supply 24V 35 W
EAN 4007841 091491	Aluminium ground spike 24V
EAN 4007841 089313	Cross Connector 24V
EAN 4007841 089306	T-Connector 24V

## Dimension Drawing

