

24V-Garden LED light

# Spot Way SC 24V

with motion detector & Bluetooth  
EAN 4007841 089320  
Article number 089320



outdoor spot



Plug & Play - easy to install



Low-voltage system



Infrared sensor 90°



max. 10 m



Bluetooth Mesh



Settings via App



IP65



Light source not exchangeable



CE

## Function description

The stand and path light for your outdoor area. As part of the 24V garden lighting system, the "Spot Way SC 24V" illuminates garden paths, flower beds, and areas around the house with pleasant light. The stylish and functional LED spotlight provides 363 lm light output at a low 7,93 W and ensures orientation and atmosphere in the outdoor area. The light head can be tilted up to 90° vertically. Includes infrared sensor (90° detection) with a 10 m range. Power supply is not included.

## Technical specifications

Dimensions (L x W x H)	140 x 226 x 572 mm
With lamp	Yes, STEINEL LED system
Manufacturer's Warranty	3 years
Settings via	Bluetooth Mesh
With remote control	No
Version	with motion detector & Bluetooth
PU1, EAN	4007841089320
Application, place	Outdoors
Application, room	outdoors, garden, terrace / balcony
Colour	Anthracite
includes sheet of self-adhesive numbers	No
Package content	1
Installation site	Floor
IP-rating	IP65
Ambient temperature	from -20 up to 40 °C
Housing material	Aluminium

Luminous flux total product	363 lm
Measured luminous flux (360°)	363 lm
Colour temperature	all colors + 1800-4000 K
Colour variation LED	SDCM3
Lamp	LED cannot be replaced
Service life LED L70B50 (25°)	> 60000 h
Soft light start	Yes
Continuous light	selectable
Functions	DIM function, Motion sensor, Color temperature change, Light sensor, Normal / test mode, Push button configuration
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Basic light level function	Yes
Basic light level function time	5s-60 min
Main light adjustable	10 – 100 %

# Spot Way SC 24V

with motion detector & Bluetooth  
EAN 4007841 089320  
Article number 089320



## Technical specifications

Cover material	PC structured	Twilight setting TEACH	Yes
Output	7.93 W	Interconnection	Yes
Average rated life expectancy of power supply unit at 25°C	> 60000 h	Basic light level function in per cent	10 – 100 %
Slave modeselectable	Yes	Basic light level function percentage, from	10 %
Sneak-by guard	No	Basic light level function percentage, up to	100 %
Capability of masking out individual segments	No	Interconnection via	Bluetooth Mesh
Electronic scalability	No	R9-Farbwiedergabeindex	60
Mechanical scalability	No	Detection angle	90 °
Reach, radial	$r = 2 \text{ m (3 m}^2)$	Product category	24V-Garden LED light
Reach, tangential	$r = 10 \text{ m (79 m}^2)$	Ausführung des Betriebsgeräts	with sensor & Bluetooth
		Cord length	0.65 m

## Accessories

EAN 4007841 089283	Cable 24V
EAN 4007841 089252	Power Supply 24V
EAN 4007841 089269	Power Supply 24V
EAN 4007841 089306	T-Connector 24V
EAN 4007841 089313	Cross Connector 24V
EAN 4007841 088620	Wireless pushbutton TapDuo C

## Dimension Drawing

