

HF 360-2

COM1 - concealed black
EAN 4007841 086770
Article number 086770



high frequency
sensor 360°



max. Ø 12 m

2000 W

max. 2000 W



IP20



ideal 1 - 2,5 m



Bluetooth Mesh



5 sec - 60 min



iQ-mode

5 years

manufacturer's
warranty steinel.de/
garantie



CE

Function description

Smart surveillance professional. The HF 360-2 from the new Control PRO 2 range. Modern look and intelligent 360° HF sensor technology – ideal for stairwells and toilet facilities with cubicles. Conveniently adjusted and interconnected via Bluetooth. Interfaces: COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave). Mounting height up to 4 m. Reach: 12 m.

Technical specifications

Dimensions (L x W x H)	61 x 103 x 103 mm
Manufacturer's Warranty	5 years
Settings via	Bluetooth Mesh
With remote control	No
Version	COM1 - concealed black
PU1, EAN	4007841086770
Type	Presence detector
Application, place	Indoors
Application, room	function room / ancillary room, kitchenette, stairwell, WC / washroom, Indoors
Colour	black
Colour, RAL	9005
Includes corner wall mount	No
Installation site	ceiling
Installation	Concealed wiring, Ceiling
IP-rating	IP20
Ambient temperature	from -25 up to 50 °C

Mounting height	2,5 – 4 m
Mounting height max.	4,00 m
Optimum mounting height	2,8 m
HF-system	5,8 GHz
Detection	also through glass, wood and stud walls
Detection angle	360 °
Angle of aperture	160 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	Ø 12 m (113 m ²)
Reach, tangential	Ø 12 m (113 m ²)
Transmitter power	< 1 mW
Functions	Semi-/fully automatic, Master/slave override, Neighbouring group

HF 360-2

COM1 - concealed black
EAN 4007841 086770
Article number 086770




Technical specifications

Material	Plastic		function, Normal / test mode, Presence function
Mains power supply	220 – 240 V / 50 – 60 Hz	Twilight setting	2 – 2000 lx
Switching output 1, resistive	2000 W	Time setting	10 s – 60 Min.
Switching output 1, floating	No	Basic light level function	No
Switching output 1, low-voltage halogen lamps	1000 VA	Main light adjustable	No
Power consumption	0,5 W	Twilight setting TEACH	Yes
Technology, sensors	High frequency	Constant-lighting control	No
Voltage range (min)	220 V	Interconnection	Yes
Voltage range (max)	240 V	Interconnection via	Bluetooth Mesh
		Product category	Presence detector

HF 360-2


COM1 - concealed black
EAN 4007841 086770
Article number 086770

Detection Zone



Possible mounting height: 2,50 m – 4,00 m
Orange: radial and tangential

Dimension Drawing



Master circuit diagram

