

HF 360-2

V3.5 KNX - concealed black
EAN 4007841 086749
Article number 086749



high frequency
sensor 360°



max. Ø 12 m



KNX



IP20



ideal 1 - 2,5 m



10 sec - 30 min



temperature



air humidity



iQ-mode

5 years

manufacturer's
warranty steinel.de/
garantie

Function description

Smart surveillance professional. The HF 360-2 from the new Control PRO 2 range. Modern look and intelligent 360° HF sensor technology – ideal for stairwells and toilet facilities with cubicles. Conveniently adjusted and interconnected via Bluetooth. Interfaces: COM1, COM2, DALI-2 APC, DALI-2 IPD, KNX, IP and BT IPD (Slave). Mounting height up to 4 m. Reach: 12 m. Light measurement is not possible with the black sensors. An external light meter must be integrated via Bluetooth or KNX for this purpose.

Technical specifications

Dimensions (L x W x H)	60 x 103 x 103 mm	Mounting height max.	4,00 m
With motion detector	Yes	Optimum mounting height	2,8 m
Manufacturer's Warranty	5 years	HF-system	5,8 GHz
Settings via	Bluetooth, Bus	Detection	also through glass, wood and stud walls
With remote control	No	Detection angle	360 °
Version	KNX - concealed black	Angle of aperture	160 °
PU1, EAN	4007841086749	Sneak-by guard	Yes
Type	Presence detector	Capability of masking out individual segments	No
Application, place	Indoors	Electronic scalability	Yes
Application, room	function room / ancillary room, kitchenette, stairwell, WC / washroom, Indoors	Mechanical scalability	No
Colour	black	Reach, radial	Ø 12 m (113 m²)
Colour, RAL	9005	Reach, tangential	Ø 12 m (113 m²)
Includes corner wall mount	No	Transmitter power	< 1 mW
Installation site	ceiling	Twilight setting	2 – 2000 lx
Installation	Concealed wiring, Ceiling	Time setting	10 s – 1092 Min.

HF 360-2

V3.5 KNX - concealed black
EAN 4007841 086749
Article number 086749




Technical specifications

IP-rating	IP20
Ambient temperature	from -25 up to 50 °C
Material	Plastic
Mains power supply	30 V
Power supply, detail	KNX bus
With bus coupling	Yes
Technology, sensors	High frequency, Temperature, Air humidity
Voltage range (min)	30 V
Voltage range (max)	30 V
Mounting height	2,5 – 4 m

Main light adjustable	Yes
Twilight setting TEACH	Yes
Constant-lighting control	Yes
KNX functions	Light output 4x, Constant-lighting control, Basic light level function, Photo-cell controller, Light level, HVAC output, Temperature output, Humidity output, Presence output, Day / night function, Dewpoint, Comfort
Interconnection	Yes
Interconnection via	Bluetooth Mesh
Rated current	30 mA
KNX Medium	TP 256
KNX Secure	No
Product category	Presence detector

Detection Zone



Possible mounting height: 2,50 m – 4,00 m
Orange: radial and tangential

Dimension Drawing

