




LED

3000 K



30 years (Ø 4,5h / day)

3000K warm-white

infrared sensor 180°

max. radius 10 m

2.4 / 5 GHz WiFi

Intercom system

Camera

inclusive

Light source not exchangeable

Control gear not exchangeable

Function description

Smart. Safe. Intelligent. The L 625 CAM SC combines outdoor light, motion detector, surveillance camera and intercom in one. The 180° infrared motion sensor with a 10 m range reliably detects any movement. The warm white lighting brightens any entrance area and the 180° horizontally swivelling camera delivers images and video recordings in up to 2K via WiFi (2.4/5 GHz, WiFi 6, WPA3) to your smartphone – no matter where you are. Recordings are saved locally on the included 16 GB microSD card. The L 625 CAM SC is now easy and quick to set up via Bluetooth. With the STEINEL CAM app, you can communicate with visitors, control all functions individually, and use the masking function to define which areas should be monitored and which not. This way, you can protect your home intelligently – your way – without cloud, without subscription.

Technical specifications

Dimensions (L x W x H)	131 x 78 x 305 mm	Reach, tangential	r = 10 m (157 m ²)
With lamp	Yes, STEINEL LED system	Photo-cell controller	Yes
Manufacturer's Warranty	3 years	Luminous flux total product	925 lm
Settings via	Wi-Fi	Measured luminous flux (360°)	925 lm
With remote control	No	Total product efficiency	67 lm/W
Version	Anthracite	Colour temperature	3000 K
PU1, EAN	4007841092597	Lamp	LED cannot be replaced
Application, place	Outdoors	Service life LED L70B50 (25°)	> 36000 h
Application, room	recreation room, front door, courtyard & driveway	Base	without
Colour	Anthracite	LED cooling system	Passive Thermo Control
includes sheet of self-adhesive numbers	No	Soft light start	No
Package content	1	Continuous light	selectable
Installation site	wall	Functions	Motions sensor, Intercom system, Camera
Impact resistance	IK03	Twilight setting	10 – 10000 lx

Technical specifications

IP-rating	IP44	Time setting	60 s – 15 Min.
Protection class	I	Basic light level function	Yes
Ambient temperature	from -10 up to 40 °C	Main light adjustable	30 - 100 %
Housing material	Aluminium	Twilight setting TEACH	No
Cover material	Glass opal	Interconnection	No
Mains power supply	220 – 240 V / 50 – 60 Hz	Basic light level function in per cent	10 – 40 %
Output	14 W	Basic light level function percentage, from	10 %
Average rated life expectancy of power supply unit at 25°C	> 36000 h	Basic light level function percentage, up to	40 %
Mounting height max.	2,00 m	Interconnection via	Wi-Fi
Sneak-by guard	No	Colour Rendering Index CRI	= 80
Capability of masking out individual segments	No	Optimum mounting height	2 m
Electronic scalability	Yes	Detection angle	180 °
Mechanical scalability	No	Product category	Sensor-switched LED outdoor light
Reach, radial	r = 2 m (6 m ²)		

Sensor-switched LED outdoor light

L 625 CAM SC


Anthracite

EAN 4007841 092597

Article number 092597



Detection Zone




Possible mounting height: 1,80 m - 2,00 m

Orange: radial

Black: tangential

Dimension Drawing



Master circuit diagram

