

# IR Quattro HD-2 24m

COM1 - in-ceiling installation white  
EAN 4007841 079406  
Article number 079406



infrared sensor



ideal 2,5 - 10 m



2 - 2000 lux



5 sec - 60 min



Settings via App



movement



max. 8m x 8m presence



brightness

Teach



Teach mode

CE

## Function description

Designed for the finest detection in the largest detection area among our infrared presence detectors. Ideal for open-plan offices or classrooms. Infrared presence detector IR Quattro HD-2 with 360° detection capability and 5,200 switching zones. Wireless setting, adjustment and interconnection via Bluetooth. Pyro sensor individually controllable. For installation in ceilings (COM1, KNX V3.5) as well as for concealed and surface mounting (COM1, COM2, DALI-2 IPD, KNX V3.5, IP und BT IPD). Measured variables: Presence function and light level as well as temperature and humidity on the basis of IP, KNX and DALI-2 IPD. Max. mounting height 10 m. Reach: 81 m<sup>2</sup> (radial), 576 m<sup>2</sup> (tangential).

# IR Quattro HD-2 24m

COM1 - in-ceiling installation white  
EAN 4007841 079406  
Article number 079406



## Technical specifications


Dimensions (L x W x H)	106 x 103 x 103 mm	LED lamps > 2 W < 8 W	300 W
Manufacturer's Warranty	5 years	LED lamps > 8 W	600 W
Settings via	Bluetooth Mesh, App, Potentiometers, Smartphone	Capacitive load in $\mu$ F	176 $\mu$ F
With remote control	No	Power consumption	0,3 W
Version	COM1 - in-ceiling installation white	Technology, sensors	Light sensor, passive infrared
PU1, EAN	4007841079406	Mounting height	2,50 – 10,00 m
Type	Presence detector	Mounting height max.	10,00 m
Application, place	Indoors	Optimum mounting height	2,8 m
Application, room	lecture hall, classroom, open-plan office, high-bay warehouse, production facilities, conference room / meeting room, duty room, recreation room, changing room, reception / lobby, sports hall, multi-storey / underground car park, dining hall / staff restaurant, Indoors	Detection angle	360 °
Colour	white	Sneak-by guard	Yes
Colour, RAL	9003	Capability of masking out individual segments	Yes
Includes corner wall mount	No	Electronic scalability	Yes
Installation site	ceiling	Mechanical scalability	Yes
Installation	In-ceiling installation, Ceiling	Reach, radial	9 x 9 m (81 m <sup>2</sup> )
IP-rating	IP20	Reach, tangential	24 x 24 m (576 m <sup>2</sup> )
Ambient temperature	from -20 up to 50 °C	Reach, presence	9 x 9 m (81 m <sup>2</sup> )
Material	Plastic	Switching zones	5200 switching zones
Mains power supply	220 – 240 V / 50 – 60 Hz	Functions	Group parameterisation, Semi-/fully automatic, Manual ON / ON-OFF, Neighbouring group function, Normal / test mode, Lighting scenario
Switching output 1, resistive	2000 W	Twilight setting	2 – 2000 lx
Switching output 1, number of LEDs / fluorescent lamps	8 pcs.	Time setting	5 s – 60 Min.
Switching output 1, floating	No	Basic light level function	No
Fluorescent lamps, electronic ballast	1500 W	Main light adjustable	No
Fluorescent lamps, uncorrected	1000 VA	Twilight setting TEACH	Yes
Fluorescent lamps, series-corrected	400 VA	Constant-lighting control	No
Fluorescent lamps, parallel-corrected	1000 VA	Interconnection	Yes
Switching output 1, low-voltage halogen lamps	2000 VA	Interconnection via	Bluetooth Mesh
LED lamps < 2 W	100 W	Product category	Presence detector

# IR Quattro HD-2 24m


COM1 - in-ceiling installation white  
EAN 4007841 079406  
Article number 079406



## Detection Zone




## Dimension Drawing 1



Possible mounting height: 2,50 m - 10,00 m  
Orange: presence  
Black: tangential

## Dimension Drawing 2



## Master circuit diagram

