

# RS PRO 6100 circular SC

with motion detector

EAN 4007841 089832

Article number 089832



LED

Bluetooth®  
MESH

HF digital2



4000 K



10-100%

10-100%



2 - 2000 lux



5 sec - 60 min

## Function description

Our circular economy miracle. Our RS PRO 6100 circular SC luminaire is pioneering in terms of efficiency and sustainability. The low-maintenance, modular luminaire is made from up to 98% recycled plastic. Should components designed for a particularly long service life, such as the sensor, power supply unit or LED board, ever fail, they can be replaced. The basic lighting function and intelligent sensor technology reduce the operating times of the lighting components, further increasing their service life. Whether in industrial environments, car parks and underground garages or in storage and basement areas – the wide beam angles always guarantee maximum light output. And the intelligent sensor technology, in conjunction with Connected Lighting via Bluetooth, always ensures maximum energy efficiency. And to close the circle, thanks to the take-back concept, every luminaire is returned to the material cycle at the end of its long product life. You have our word!

## Technical specifications

Dimensions (L x W x H)	1200 x 90 x 80 mm
With lamp	Yes, STEINEL LED system
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	App, Bluetooth, Bluetooth Mesh
With remote control	No
Version	with motion detector
PU1, EAN	4007841089832
Application, place	Indoors
Application, room	corridor / aisle, function room / ancillary room, warehouse, multi-storey / underground car park, production facilities, stairwell, changing room, WC / washroom
Colour	grey
Installation site	ceiling, wall

Reach, radial	Ø 8 m (50 m <sup>2</sup> )
Reach, tangential	Ø 8 m (50 m <sup>2</sup> )
Photo-cell controller	Yes
Transmitter power	< 1 mW
Colour temperature	4000 K
Colour variation LED	SDCM3
Lamp	LED can be replaced
Base	without
LED cooling system	Passive Thermo Control
Soft light start	Yes
Continuous light	selectable
Functions	Motions sensor, DIM function, Dimmkurve individuell einstellbar, Adjustable fade time when switching on and off, Semi-/fully automatic, Light sensor, Neighbouring group

**RS PRO 6100 circular SC**

with motion detector

EAN 4007841 089832

Article number 089832

**Technical specifications**

Installation	Surface wiring, Ceiling, Wall	function, Encrypted communication, Timer
Impact resistance	IK08	2 – 2000 lx
IP-rating	IP65	5 s – 60 Min.
Protection class	I	Yes
Ambient temperature	from -20 up to 40 °C	5s-60 min, Brightness-controlled
Housing material	Plastic	0 - 100 %
Cover material	PC structured	Yes
Mains power supply	220 – 240 V / 50 – 60 Hz	Master/master
Power consumption	0,3 W	Bluetooth Mesh
Mounting height max.	3,50 m	10 – 100 %
HF-system	24 GHz	28 W
Slave modeselectable	Yes	160 °
Electronic scalability	Yes	360 °
Mechanical scalability	No	Sensor-switched LED indoor light

# RS PRO 6100 circular SC


with motion detector

EAN 4007841 089832


Article number 089832



## Detection Zone



## Dimension Drawing



Possible mounting height: 2,00 m – 3,50 m

Orange: radial and tangential

## Light with neutral conductor

