

LED floodlight without sensor

Spot Garden N

with twilight switch

EAN 4007841 058692

Article number 058692



LED

20.000 h

3000 K

3000K warm-white



38°



Twilight switch



IP44



2 - 1000 lux



Light source
replaceable by end
user



Control gear not
exchangeable

3 years

manufacture's
warranty steinel.de/
garantie



CE

Function description

The spike light for the garden. The "Spot Garden N" competently sets off green spaces and flower beds around the home. Equally as attractive as it is practical, the LED spot with photo-cell controller provides 512 lm of light from 7,86 W and can be tilted through up to 90°. The light-level sensor switches automatically switches light ON at dusk and OFF again in the morning. Includes power cord (2.5 m) and lamp.

Technical specifications

Dimensions (L x W x H)	140 x 69 x 369 mm
With lamp	Yes, LED lamp
With motion detector	No
Manufacturer's Warranty	3 years
Settings via	Potentiometers
Version	with twilight switch
PU1, EAN	4007841058692
Application, place	Outdoors
Application, room	outdoors, garden
Colour	Anthracite
Includes corner wall mount	No
Installation site	Ground spike
Installation	Ground spike
Impact resistance	IK03
IP-rating	IP44
Protection class	I
Ambient temperature	from -20 up to 40 °C

Slave mode selectable	Yes
Photo-cell controller	Yes
Luminous flux total product	512 lm
Measured luminous flux (360°)	512 lm
Total product efficiency	65,1 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM5
Lamp	LED can be replaced
Service life LED L70B50 (25°)	> 20000 h
Soft light start	No
Continuous light	selectable
Twilight setting	2 – 1000 lx
Basic light level function	No
Main light adjustable	No
Twilight setting TEACH	No
Interconnection	No
Output	7,86 W

<https://www.steinel.de>

Subject to technical modifications

07.2026 Page 1 from 2

LED floodlight without sensor

Spot Garden N

with twilight switch

EAN 4007841 058692

Article number 058692



Technical specifications

Housing material	Aluminium
Cover material	Plastic, transparent
Mains power supply	220 – 240 V / 50 – 60 Hz

Colour Rendering Index CRI	= 81
Product category	LED floodlight without sensor

Dimension Drawing

