

Sensor-switched LED floodlight


Spot Way SC

with motion detector & Bluetooth
EAN 4007841 058661
Article number 058661



LED

3000 K



20.000 h

3000K warm-white

38°

Infrared sensor 90°

max. 10 m

Twilight switch

IP44

Light source
replaceable by end
user

Control gear not
exchangeable

2 - 1000 lux

Function description

Timeless look. Quickly interconnected. The elegant, swivelling ground spotlight (57 cm) with 90° infrared sensor stylishly and brightly sets off driveways, garden parts etc. with 512 lm of warm-white light at 3000 K. Convenient interconnection, adjustment and control via free app. This makes child's play of selecting time and twilight settings, ON/OFF times as well as grouping lights. Includes mains plug (2.5 m) and lamp.

Technical specifications

Dimensions (L x W x H)	226 x 140 x 572 mm
With lamp	Yes, LED lamp
With motion detector	Yes
Manufacturer's Warranty	3 years
Settings via	Bluetooth
Version	with motion detector & Bluetooth
PU1, EAN	4007841058661
Application, place	Outdoors
Application, room	outdoors, garden
Colour	Anthracite
Includes corner wall mount	No
Installation site	Stand mounted
Installation	Stand mounted
Impact resistance	IK03
IP-rating	IP44
Protection class	I
Ambient temperature	from -20 up to 40 °C

Reach, radial	r = 2 m (3 m ²)
Reach, tangential	r = 10 m (79 m ²)
Photo-cell controller	Yes
Luminous flux total product	512 lm
Measured luminous flux (360°)	512 lm
Total product efficiency	64,8 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM5
Lamp	LED can be replaced
Service life LED L70B50 (25°)	> 20000 h
Soft light start	No
Continuous light	selectable, 4h
Functions	Manual ON / ON-OFF, Timer, Master/slave override
Twilight setting	2 - 2000 lx
Time setting	5 s - 60 Min.
Basic light level function	No

Spot Way SC

with motion detector & Bluetooth
EAN 4007841 058661
Article number 058661

Technical specifications


Housing material	Aluminium	Main light adjustable	No
Cover material	Plastic, transparent	Twilight setting TEACH	Yes
Mains power supply	220 – 240 V / 50 – 60 Hz	Interconnection	Yes
Slave modeselectable	Yes	Interconnection via	Bluetooth
Sneak-by guard	No	Output	7,9 W
Capability of masking out individual segments	No	Colour Rendering Index CRI	= 81
Electronic scalability	No	Detection angle	90 °
Mechanical scalability	No	App	STEINEL Connect App
		Product category	Sensor-switched LED floodlight

Accessories

EAN 4007841 088620

Wireless pushbutton TapDuo C

Detection Zone



Possible mounting height: -
Orange: radial
Black: tangential

Dimension Drawing

