

Sensor-switched LED floodlight


Spot Garden SC

Sensor Connect
EAN 4007841 058685
Article number 058685



LED

3000 K



20.000 h

3000K warm-white

38°

Infrared sensor 90°

max. 10 m

IP44

2 - 2000 lux (via App)

Light source
replaceable by end user

Control gear not
exchangeable

manual override

Function description

Interconnected garden enjoyment. The Spot Garden SC ground spotlight with 90° infrared sensor simply pushes into the earth and provides versatile illumination all around the home. The LED spot is conveniently set, interconnected and controlled via Bluetooth by app. ON and OFF times, twilight and time settings as well as creating lighting group – all not a problem. 512 lm, 7,9 W, 3000 K. Includes 2.5 m mains plug and GU-10 LED.

Technical specifications

Dimensions (L x W x H)	140 x 69 x 369 mm
With lamp	Yes, LED lamp
With motion detector	Yes
Manufacturer's Warranty	3 years
Settings via	Bluetooth
Version	Sensor Connect
PU1, EAN	4007841058685
Application, place	Outdoors
Application, room	outdoors, garden
Colour	Anthracite
Includes corner wall mount	No
Installation site	Ground spike
Installation	Ground spike
Impact resistance	IK03
IP-rating	IP44
Protection class	I
Ambient temperature	from -20 up to 40 °C

Reach, radial	$r = 2 \text{ m (3 m}^2)$
Reach, tangential	$r = 10 \text{ m (79 m}^2)$
Photo-cell controller	Yes
Luminous flux total product	512 lm
Measured luminous flux (360°)	512 lm
Total product efficiency	64,8 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM5
Lamp	LED can be replaced
Service life LED L70B50 (25°)	> 20000 h
Soft light start	No
Continuous light	selectable
Functions	Manual ON / ON-OFF, Timer, Master/slave override
Twilight setting	2 – 2000 lx
Time setting	5 s – 60 Min.
Basic light level function	No

Spot Garden SC

Sensor Connect

EAN 4007841 058685

Article number 058685

Technical specifications

Housing material	Aluminium
Cover material	Plastic, transparent
Mains power supply	220 – 240 V / 50 – 60 Hz
Slave modeselectable	Yes
Sneak-by guard	No
Capability of masking out individual segments	No
Electronic scalability	No
Mechanical scalability	No


Main light adjustable	No
Twilight setting TEACH	Yes
Interconnection	Yes
Interconnection via	Bluetooth
Output	7,9 W
Colour Rendering Index CRI	= 81
Detection angle	90 °
App	STEINEL Connect App
Product category	Sensor-switched LED floodlight

Accessories

EAN 4007841 088620

Wireless pushbutton TapDuo C

Detection Zone



Possible mounting height: -

Orange: radial

Black: tangential

Dimension Drawing

