

Sensor-switched LED floodlight

# Spot Garden SC

Sensor Connect  
EAN 4007841 058685  
Article number 058685



LED

20.000 h

3000 K

3000K warm-white



38°



Infrared sensor 90°



max. 10 m




IP44



2 - 2000 lux (via App)



Light source replaceable by end user



Control gear not exchangeable



manual override

## Function description

Interconnected garden enjoyment. The Spot Garden SC ground spotlight with 90° infrared sensor simply pushes into the earth and provides versatile illumination all around the home. The LED spot is conveniently set, interconnected and controlled via Bluetooth by app. ON and OFF times, twilight and time settings as well as creating lighting group – all not a problem. 512 lm, 7,9 W, 3000 K. Includes 2.5 m mains plug and GU-10 LED.

## Technical specifications

Dimensions (L x W x H)	140 x 69 x 369 mm	Reach, radial	r = 2 m (3 m <sup>2</sup> )
With lamp	Yes, LED lamp	Reach, tangential	r = 10 m (79 m <sup>2</sup> )
With motion detector	Yes	Photo-cell controller	Yes
Manufacturer's Warranty	3 years	Luminous flux total product	512 lm
Settings via	Bluetooth	Measured luminous flux (360°)	512 lm
Version	Sensor Connect	Total product efficiency	64,8 lm/W
PU1, EAN	4007841058685	Colour temperature	3000 K
Application, place	Outdoors	Colour variation LED	SDCM5
Application, room	outdoors, garden	Lamp	LED can be replaced
Colour	Anthracite	Service life LED L70B50 (25°)	> 20000 h
Includes corner wall mount	No	Soft light start	No
Installation site	Ground spike	Continuous light	selectable
Installation	Ground spike	Functions	Manual ON / ON-OFF, Timer, Master/slave override
Impact resistance	IK03	Twilight setting	2 – 2000 lx
IP-rating	IP44	Time setting	5 s – 60 Min.
Protection class	I	Basic light level function	No
Ambient temperature	from -20 up to 40 °C		

<https://www.steinel.de>

Subject to technical modifications

03.2026 Page 1 from 2

Sensor-switched LED floodlight

# Spot Garden SC

Sensor Connect  
EAN 4007841 058685  
Article number 058685



## Technical specifications

Housing material	Aluminium
Cover material	Plastic, transparent
Mains power supply	220 – 240 V / 50 – 60 Hz
Slave mode/selectable	Yes
Sneak-by guard	No
Capability of masking out individual segments	No
Electronic scalability	No
Mechanical scalability	No


Main light adjustable	No
Twilight setting TEACH	Yes
Interconnection	Yes
Interconnection via	Bluetooth
Output	7,9 W
Colour Rendering Index CRI	= 81
Detection angle	90 °
App	STEINEL Connect App
Product category	Sensor-switched LED floodlight

## Accessories

EAN 4007841 088620

Wireless pushbutton TapDuo C

## Detection Zone



Possible mounting height: -  
Orange: radial  
Black: tangential

## Dimension Drawing

