

Solar light

XSolar SOL-O S

Silver

EAN 4007841 052652

Article number 052652



365 ^{TAGE}
LIGHT

Light 365 days of
the year

3000 K

3000K warm-white



infrared sensor
360°



max. radius 6 m



IP44



2 lux



soft light start

3 years

manufacturer's
warranty steinel.de/
garantie



No cable required



CE

Function description

The XSolar SOL-O S solar sensor light provides light around your home – without any mains connection. The light uses solar energy and requires no mains electricity during operation. It features patented intelligent microprocessor control and a high-performance lithium iron phosphate battery that supports reliable lighting throughout the year. With a 360° infrared mini sensor, a range of 6 m and 273 lm luminous flux. Includes night light function and soft light start. Available in silver and anthracite.

Technical specifications

Dimensions (L x W x H)	91 x 242 x 53 mm
With lamp	Yes, STEINEL LED system
With motion detector	Yes
Manufacturer's Warranty	3 years
Settings via	Potentiometers
Version	Silver
PU1, EAN	4007841052652
Application, place	Outdoors
Application, room	outdoors, front door, all round the building, terrace / balcony, courtyard & driveway
Colour	Silver
Installation site	wall
Impact resistance	IK03
IP-rating	IP44
Protection class	III
Ambient temperature	from -20 up to 40 °C

Luminous flux total product	273 lm
Measured luminous flux (360°)	273 lm
Colour temperature	3000 K
Colour variation LED	SDCM5
Colour Rendering Index	80-89
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Drop in luminous flux in accordance with LM80	L70B10
LED cooling system	Passive Thermo Control
Soft light start	Yes
Functions	Motions sensor
Twilight setting	2 lx
Time setting	10 s – 0,5 Min.
Basic light level function	Yes
Basic light level function time	all night
Basic light level function in per cent	3 %

<https://www.steinel.de>

Subject to technical modifications

09.2026 Page 1 from 2

Solar light

XSolar SOL-0 S

Silver

EAN 4007841 052652

Article number 052652




Technical specifications

Housing material	Aluminium
Cover material	Plastic, structured
Power supply, detail	Solar supply, no mains power required, Lithium-iron-phosphate rechargeable battery 2x 2000 mAh
Mounting height max.	2,50 m
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, radial	Ø 4 m (13 m ²)
Reach, tangential	Ø 12 m (113 m ²)
Photo-cell controller	Yes

Basic light level function percentage, from	3 %
Basic light level function percentage, up to	3 %
Output	3,3 W
Battery charge	ab 0°
Akku-Funktion	ab - 20
Detection angle	360 °
Product category	Solar light

Detection Zone



Dimension Drawing

