

TS basic

Anthracite

EAN 4007841 099688

Article number 099688



Twilight switch



15 lux



IP54

1000 W

1000 W max.

5 years

manufacturer's warranty steinel.de/
garantie

CE

Function description

Stylish twilight switch. The strikingly unobtrusive NightmatIQ twilight switch impresses with its sleek, minimalist design and automatically ensures perfect lighting night after night. When the set twilight threshold is reached, the twilight switch springs into action and switches on all connected lights simultaneously. This allows house fronts, properties, gardens, shop windows or other areas to be reliably illuminated just as dusk falls – without you having to lift a finger. Then, hours later as dawn breaks, the lights switch off again all by themselves. Thanks to NightmatIQ, existing lights that were previously switched on manually can be converted to automatic operation in no time at all. The twilight threshold can be adjusted as required using a potentiometer control, from 1 to 75 lux ambient brightness. Connection is via a plug-in terminal. Whether it's rain, storm or snow – the NightmatIQ operates reliably in all weather conditions thanks to its IP 54 protection rating. The twilight switch is available in white and anthracite.

Technical specifications

Dimensions (L x W x H)	38 x 95 x 95 mm	Ambient temperature	from -20 up to 40 °C
With motion detector	No	Mains power supply	220 – 240 V / 50 – 60 Hz
Manufacturer's Warranty	5 years	LED lamps > 2 W < 8 W	250 W
Settings via	Potentiometers	LED lamps > 8 W	250 W
With remote control	No	Technology, sensors	Mixed light metering
Version	Anthracite	Voltage range (min)	220 V
PU1, EAN	4007841099688	Voltage range (max)	240 V
Type	Photo-cell controller	Twilight setting	1 – 75 lx
Application, place	Outdoors	Basic light level function	No
Application, room	outdoors, front door, courtyard & driveway, indoors, all round the building, terrace / balcony	Main light adjustable	No
Colour	Anthracite	Constant-lighting control	No
Installation site	wall	Interconnection	Yes
Installation	Surface wiring, Wall	Interconnection via	Cable
		Product category	Photoelectric lighting controller

TS basic

Anthracite

EAN 4007841 099688

Article number 099688



Technical specifications

IP-rating

IP54

Dimension Drawing

