

Motion detector

IS 3360 MX Highbay

DALI - surface-mounted installation, square

EAN 4007841010577



Function description

A head for heights. Powerful reach. Reliable. IS 3360 MX Highbay motion detector – ideal for high ceilings in industrial buildings or commercial properties. For mounting heights of up to 14 m. High-precision 360° infrared sensor. Maximum reach: 18 m. For watching over up to 1000 sq.m. Available as square surface-mounted and concealed version.

Technical specifications

Type	Motion detectors
Dimensions (L x W x H)	95 x 95 x 65 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	passive infrared
Application, place	Indoors
Application, place, room	high-bay warehouse, sports hall
Type of installation	Surface wiring
Switching zones	1416 switching zones
Electronic scalability	No
Mounting height	4,00 – 14,00 m
Optimum mounting height	12 m
Detection angle	360 °
Angle of aperture	45 °
Capability of masking out individual segments	Yes
Reach, radial	Ø 12 m (113 m ²)
Reach, tangential	Ø 36 m (1018 m ²)
Twilight setting TEACH	Yes
Twilight setting	2 – 1000 lx

Motion detector

IS 3360 MX Highbay

DALI - surface-mounted installation, square

EAN 4007841010577

Technical specifications

Time setting	5 sec – 15 min
Control output, DALI	Broadcast 1x30 electronic ballasts
Constant-lighting control	Yes
Basic light level function	Yes
Basic light level function in per cent	10 – 50 %
Basic light level function time	1-30 min, all night
Basic light level function percentage, from	10 %
Basic light level function percentage, up to	50 %
With remote control	No
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9003
Manufacturer's Warranty	5 years
Version	DALI - surface-mounted installation, square
PU1, EAN	4007841010577

Data sheet



Motion detector

IS 3360 MX Highbay

DALI - surface-mounted installation, square

EAN 4007841010577

Mood image

