

## Motion detector

# IS 3360

DALI - surface-mounted installation, square  
EAN 4007841010560



## Function description

Higher, further, faster. Infrared motion detector IS 3360 for indoors and out, ideal for watching over high spaces and large areas, such as multi-storey and underground car parks, installation height up to 4 m, 360° angle of coverage, reach 20 m max. (tangential), large terminal compartment for easy installation. Available either in round or square surface-mounted and concealed version.

## Technical specifications

|   |   |
|---|---|
| Type  | Motion detectors  |
| Dimensions (L x W x H)                        | 95 x 95 x 65 mm   |
| Mains power supply                            | 220 – 240 V , 50 / 60 Hz  |
| Sensor Technology                             | passive infrared  |
| Application, place                            | outdoors, Indoors   |
| Application, place, room                      | sports hall, side room, stairwell, wc, washroom, multi-storey car park, underground car park, warehouse, equipment room |
| Type of installation                          | Surface wiring  |
| Switching zones                               | 1416 switching zones  |
| Electronic scalability                        | No  |
| Mechanical scalability                        | No  |
| Mounting height                               | 2,50 – 4,00 m   |
| Optimum mounting height                       | 2,8 m   |
| Detection angle                               | 360 °   |
| Angle of aperture                             | 180 °   |
| Sneak-by guard                                | Yes   |
| Capability of masking out individual segments | Yes   |
| Reach, radial                                 | Ø 10 m (79 m <sup>2</sup> )   |

# Data sheet



Motion detector

## IS 3360

DALI - surface-mounted installation, square

EAN 4007841010560

### Technical specifications

|  |   |
|--|---|
| Reach, tangential                            | Ø 40 m (1257 m <sup>2</sup> )               |
| Reach, presence                              | Ø 3 m (7 m <sup>2</sup> )                   |
| Twilight setting TEACH                       | Yes   |
| Twilight setting                             | 2 – 1000 lx                                 |
| Time setting                                 | 5 sec – 15 min                              |
| Control output, DALI                         | Broadcast 1x30 electronic ballasts          |
| Constant-lighting control                    | Yes   |
| Basic light level function                   | Yes   |
| Basic light level function in per cent       | 10 – 50 %                                   |
| Basic light level function time              | 1-30 min, all night                         |
| Basic light level function percentage, from  | 10 %  |
| Basic light level function percentage, up to | 50 %  |
| With remote control                          | No  |
| Interconnection                              | Yes   |
| IP rating                                    | IP54  |
| Material                                     | Plastic                                     |
| Ambient temperature                          | -20 – 50 °C                                 |
| Colour                                       | white                                       |
| Colour, RAL                                  | 9003  |
| Manufacturer's Warranty                      | 5 years                                     |
| Version                                      | DALI - surface-mounted installation, square |
| PU1, EAN                                     | 4007841010560                               |

# Data sheet



Motion detector

## IS 3360

DALI - surface-mounted installation, square

EAN 4007841010560

Mood image

